

# *Hex* 4.2 User Manual

---

Macromolecular Docking Using Spherical Polar Fourier Correlations  
Copyright © 2003 David W. Ritchie



Dave Ritchie  
Department of Computing Science  
University of Aberdeen  
Aberdeen AB24 3UE, Scotland, UK

---

# Table of Contents

<b>1</b>	<b>Introduction</b>	<b>1</b>
1.1	What The Heck Is <i>Hex</i> ?	1
1.2	How To Read This Manual	2
1.3	New Features In Version 4.2	3
<b>2</b>	<b>Getting Started</b>	<b>4</b>
2.1	Short-Cut Buttons	4
2.2	Function Buttons	5
2.3	Keyboard Keys	6
<b>3</b>	<b>Molecular Graphics</b>	<b>7</b>
3.1	Basic Display Styles	7
3.2	Solid Models	8
3.3	Cartoons	8
3.4	Solid Surfaces	9
3.5	Spherical Harmonic Surfaces	10
3.6	Dot Surfaces	11
3.7	Changing The Scene Origin	12
3.8	Clipping The Scene	12
3.9	Animation	13
3.10	Full Screen Mode	14
3.11	Stereo Displays	14
<b>4</b>	<b>Manoeuvring Molecules</b>	<b>16</b>
4.1	Editing Orientations	16
4.2	Editing Centroids	17
<b>5</b>	<b>Docking Molecules</b>	<b>18</b>
5.1	Rotational Search	19
5.2	Other Search Modes	19
5.3	Radial Filters	20
5.4	Docking Examples	20
5.5	Calculating Bumps	22
5.6	Molecular Mechanics Refinement	22
5.7	Clustering Docking Results	23
5.8	Saving Docking Results	23
5.9	Docking Multiple Structures	24
5.10	Docking Very Large Molecules (Macro Docking)	24
5.11	Additional Docking Parameters	25
5.12	Molecular Matching	25

<b>6</b>	<b>Miscellaneous</b>	<b>27</b>
6.1	Macros	27
6.2	Hetero Atoms	29
6.3	Hardcopy Output	30
6.4	Compressed Files	30
6.5	Environment Variables	30
6.6	Command Line Options	31
6.6.1	Loading Three Structures Together	32
6.6.2	Loading And Superposing Two Structures	32
6.6.3	Docking With Macro File And Log File	32
6.6.4	Docking With File I/O Redirection	32
6.6.5	Serialising Several Batch Jobs	32
6.6.6	Using <i>Hex</i> As a Web Browser	32
6.7	Examples Directory	32
6.8	Bugs And Known Limitations	33
6.8.1	No Multi-Processing on MS-Windows	33
6.8.2	GUI and Graphics Freeze During Docking	33
6.8.3	Macros	34
6.8.4	Non-Standard Residues	34
6.8.5	Hardcopy Fonts	34
6.8.6	Colouring Multiple Models	34
6.9	The Test Functions	34
6.10	Technical Information	35
6.11	Caveats	36
6.12	Contacts	36
6.13	Acknowledgements	36
6.14	References	37
6.15	Citing <i>Hex</i>	38
<b>Appendix A</b>	<b>Licences</b>	<b>39</b>
A.1	Hex Licence	39
A.2	Stride Licence	41
<b>Appendix B</b>	<b>Installation Guide</b>	<b>42</b>
B.1	Microsoft Windows Installation	42
B.2	Unix/Linux Installation	42
<b>Appendix C</b>	<b>Feature History</b>	<b>45</b>
C.1	New Features In Version 4.1	45
C.2	New Features In Version 4.0	45
C.3	New Features In Version 3.4	45
C.4	New Features In Version 3.3	45
C.5	New Features In Version 3.2	45
C.6	New Features In Version 3.1	46
C.7	New Features In Version 3.0	46

Appendix D   nVidia Stereo Configuration . . . . .	48
Appendix E   Frequently Asked Questions . . . . .	49
Subject Index . . . . .	56

# 1 Introduction

“hex /heks/ *v.* & *n.* *US – v.* **1.** practise witchcraft. **2.** bewitch. – *n.* **1.** a magic spell. **2.** a witch. [GK *hex* six].” (The Concise Oxford Dictionary).

“Why, sometimes I’ve believed as many as six impossible things before breakfast.” (Lewis Carroll).

## 1.1 What The Heck Is *Hex*?

*Hex* is an interactive molecular graphics program for calculating and displaying feasible docking modes of pairs of protein and DNA molecules. *Hex* can also calculate small-ligand/protein docking (provided the ligand is rigid), and it can superpose pairs of molecules using only knowledge of their 3D shapes.

The main thing which distinguishes *Hex* from other macromolecular docking programs and molecular graphics packages is its use of *spherical polar Fourier correlations* to accelerate the docking and superposition calculations. The graphical nature of *Hex* came about largely because I wanted to visualise the results of such docking calculations in a natural and seamless way, without having to export unmanageably many (and usually quite big) coordinate files to one of the many existing molecular graphics packages. For this reason, the graphical capabilities in *Hex* are relatively primitive compared to commercial packages, although these days one can do quite a lot with a few calls to OpenGL. Nonetheless, if your main interest is in modelling *macromolecular docking*, then please read on. *Hex* may have something new to offer!

In *Hex*’s docking calculations, each molecule is modelled using 3D parametric functions which are used to encode both surface shape and electrostatic charge and potential distributions. The parametric functions are based on expansions of real orthogonal spherical polar basis functions. Essentially, this allows each property to be represented by a vector of coefficients. *Hex*’s surface shape representation uses a novel 3D *surface skin* model of protein topology, whereas the electrostatic model is derived from classical electrostatic theory. By writing an expression for the *overlap* of pairs of parametric functions, one can derive an expression for a docking score as a function of the six degrees of freedom in a rigid body docking search. With suitable scaling factors, this docking score can be interpreted as an interaction energy, which we seek to minimise. Due to the special orthogonality property of the basis functions, the *correlation* (or *overlap* as a function of translation/rotation operations) between a pair of 3D functions can be calculated using expressions which involve only the original expansion coefficients. In many respects, this approach is similar to conventional fast Fourier transform (FFT) docking methods which use a Cartesian grid to perform the Fourier transforms. However, the FFT approach only accelerates a docking search in three (translational) degrees of freedom whereas with a spherical polar approach, we can both translate (with some effort) and rotate (relatively easily) the coefficient vectors to generate and evaluate candidate docking orientations in what is effectively a six dimensional Fourier correlation.

In the spherical polar approach, it is natural to assign the six rigid body degrees of freedom as five Euler rotation angles and an intermolecular separation. Thus, in complete contrast to the FFT approach, the rotational part of a docking search is the “easy bit”

and modelling translations becomes the “hard part”. Fortunately, however, only a few translations (typically about 40 steps of 0.75 Ångstrom) are required to complete a six dimensional docking search. A further advantage of the spherical polar approach is that it is easy to constrain the docking search to one or both binding sites, when this knowledge is available, simply by constraining one or two of the angular degrees of freedom. This can reduce docking times to a matter of minutes on modern workstations. So, depending on how well a particular FFT algorithm is implemented (and on who you believe!), I claim that *Hex* is somewhere between 10 and 100 times *faster* than conventional FFT docking algorithms.

Closely related to the *protein docking problem* is the *molecular similarity problem* - i.e. how to find the relative orientation of a pair of similar molecules such that some measure of the similarity (difference) between the molecules is maximised (minimised). Both problems involve translating and rotating one or both molecules into the desired orientation. However, to a first approximation, the similarity problem can be reduced to a three dimensional rotational search by initially placing both molecules in a common coordinate system.

In fact, much of the early development of *Hex* concentrated on displaying and superposing protein surface shapes using two dimensional spherical harmonic expansions to represent surface shapes parametrically. This proved to be a fast and accurate way to superpose pairs of similar protein molecules but this type of 2D surface approach does not encode sufficient detail to give a viable docking algorithm. It was this observation that prompted the development of our 3D *density model* of molecular shape.

## 1.2 How To Read This Manual

This Manual attempts to describe the main features of *Hex* by (a) mentioning each feature at least once and (b) by giving some examples of how to use the program most effectively. In the following sections, italic text is used to refer to *Menu Item* and *Button Names*, or other important *concepts* within the program. Typewriter text is used to indicate a sequence of **menu selections** or **button actions** that are required to perform a particular function. This type of text is also used when listing the contents of some of the example files provided with the program. Bold face text is used to highlight **file** or **directory** names that refer to the installation and use of *Hex*. At various points, this Manual also contains *tips* like this:

TIP: Some parts of this Manual are quite heavy going! If you really want to read the whole thing, print out the PDF version (**hex\_manual.pdf**). Otherwise, browse it on-line as HTML using *Hex*'s **Help** button.

The graphical user interface (GUI) in *Hex* is intended to be easy to use. Generally, most actions cause an immediate effect on the display so that once you've loaded a protein or DNA molecule (preferably two such molecules), most of the program's features can be understood by experiment. If you're comfortable with this approach, go right ahead. Much of this Manual can probably be skipped. Just keep an eye on the *Messages Window* for any information messages. The parts that everyone should read are the sections on Docking (see Chapter 5 [Docking Molecules], page 18), and Superposition (see Section 5.12 [Molecular Matching], page 25). If you want to try more than just one or two docking calculations,

you should also look at the section on using macros (see Section 6.1 [Macros], page 27) and the contents of the **examples** directory (see Section 6.7 [Examples Directory], page 33). It should be noted that algorithmic details of the docking and superposition calculations are not given here. It is assumed that you have copies of the relevant publications (see Section 6.14 [References], page 37).

## 1.3 New Features In Version 4.2

*Hex* Version 4.2.

- The coordinate origin for multiple model structures is now taken from the first model (not the average of all models).
- Fixed bug for PDB files containing one structure with one MODEL keyword.
- Fixed silly bug in picking (ID) mode.
- Text output to Message Window now much faster.
- There are several undocumented features currently under development.

## 2 Getting Started

If you haven't already done so, please download and install *Hex* from *Hex's Home Page* (<http://www.biochem.abdn.ac.uk/hex/>). See Appendix B [Installation Guide], page 42 for details. It should be easier to follow this Manual if you have *Hex* up and running in front of you. Been there, done it? Great! Lets get started...

*Hex* reads protein and DNA molecular structures from PDB-format files. PDB files can be downloaded from the main Protein Data Bank repository at Rutgers University (<http://www.rcsb.org/pdb/>). Up to three PDB files can be loaded into *Hex* at any one time. These are treated as a *receptor*, a *ligand* and a *reference complex*. We'll ignore these distinctions for now and just load a single protein. Go to the *File* menu and select:

**File ... Open ... Receptor**

When you release the mouse button, a new *File Selection* menu panel should appear. Edit the *Filter* text area to specify the directory containing your PDB file(s) and press the *Filter* button. You should now see one or more PDB files listed in the *Files* box (if not, use the *File Selection* controls to navigate to the **hex/examples** directory). Pick a PDB file by double clicking on it (or by highlighting it and picking *OK*). You should now see a skeletal display of the molecule(s) from your chosen PDB file.

**TIP:** Keep all your PDB files in a single directory and set the environment variable `HEX_PDB` to point to this directory. The other file selection panels in *Hex* work in a similar manner.

Congratulations. You should now have your molecule in the centre of the scene. You should also see a small graphic in the top left of the scene that represents the  $(x,y,z)$  coordinate axes. Note that the  $z$ -axis points towards the right and the  $x$ -axis points away from you, into the scene. *Hex* uses this convention because most displays have a greater width than height and, when two molecules are loaded, its convenient to assign the  $z$ -direction to the intermolecular axis. Also, looking at a pair of molecules "side-on" somehow seems more natural(?).

Anyway, you can translate and rotate the scene with the mouse buttons. Dragging with button 1 (left button) translates the scene, and dragging with **Button 2** (middle button) rotates it. This rotation is always about an axis perpendicular to the direction of motion of **Button 2**. The right button also rotates the scene, but about different axes. A right-left motion of this button gives an anticlockwise rotation. You'll probably find that **Button 2** feels more natural for most movements but that occasionally **Button 3** is needed to complete a manoeuvre. The *Slider* on the lower left border may be used to zoom the scene in and out. The other borders around the graphics window contain various pull-down menus and control buttons. These are described in more detail below.

### 2.1 Short-Cut Buttons

The column of buttons on the right-hand border of the main window implement handy or frequently used operations. For example, *Hex* stores a *Home Position* for the scene. Pressing the *House* button at the top right border resets the scene to the current home position. If you have oriented the molecule into a view that you like, you can make this orientation the



*Home Position* position by pressing the *Lock* button, below the *Home* button. The *Unlock* button resets the *Home Position* to its the original setting (*z*-axis to the right, etc.).

The next button (the “6.6” icon) is a *text* toggle, to control the display of summary text in the graphics window. The *Axes* button (two arrows at right angles) toggles the display of the coordinate axes (useful for screen dumps). Below this is the *Intermolecular Axis* button (a double-headed arrow). This draws a white line between the centroids of the receptor and ligand molecules. If only one molecule has been loaded, a short white line is still drawn along the *z*-axis.

The *Solid Models* button toggles the display of solid models, the default being van Der Waals spheres. The type of solid model to display may be selected from the **Solid Models** control panel (see Section 3.2 [Solid Models], page 8). The *Solid Surface* button toggles the calculation and display of solid surfaces (see Section 3.4 [Solid Surfaces], page 9). Similarly, the *Harmonics* button (which looks like a balloon), toggles the calculation and display of spherical harmonic molecular surfaces (see Section 3.5 [Spherical Harmonic Surfaces], page 10), and the *Cartoon* button (which is supposed to look like part of a protein ribbon) toggles the cartoon displays.

The *Sidechain* button toggles the display of protein sidechains and DNA bases. With large molecules, rotating and translating the scene can be much faster if only the backbone trace is drawn. This is especially true if solid models or surface meshes are being displayed. The final *Solid Motion* button (the black square with an arrow) can be used to toggle whether solid shapes or just bond skeletons are drawn when moving molecules within the scene.

## 2.2 Function Buttons

The column of buttons on the left hand border of the main window implement various *picking* and *editing* functions. These operations differ from the short-cut buttons in that they generally involve changing the operating mode of the mouse. The inset icon in the top left border displays the current *mouse mode*. The default, *Pointer Mode* (a left arrow), represents the basic scene manipulation mode, described above. You can revert to this mode by pressing the *Left Arrow* button, which is the first button in the left-hand border.

The next *ID* button selects atom picking mode. In this mode, picking an atom (i.e. pressing and releasing **Button 1** over an atom) will identify the atom by displaying its chain, residue and atom numbers. The atom coordinates and charge (Q) will also be displayed in the text window. The **Graphics... Fonts** menu can be used to select the font in which atom labels are displayed. In stereo displays, picking uses the right-eye object coordinates, since most people are right-eye-dominant. Picking the same atom again will remove the atom ID label. The *Hammer* button (the last button in this border) will clear all picked ID's. This button generally acts to *undo*, or *kill*, the previous operation(s), depending on the current *mouse mode*.

Below the *ID* button is the *Manoeuvring Molecules* button (which looks like a lightning bolt), and below this is the *Origin Editing* button (a line with two crosses). This is followed by the *Clipping Mode* button (three faces of a cube) which controls scene clipping (see Section 3.8 [Clipping The Scene], page 12). Manoeuvring molecules (also called *editing*) is

something you might wish to do before running a docking calculation. Hence *editing* only makes sense when you have two molecules loaded. Go to the *File* menu and click on:

File ... Open ... Ligand

to open another molecule. You could open the same molecule for the *ligand* as you have opened for the *receptor*, in which case the two molecules will be superposed. Use the *R slider* bar on the bottom border to separate the molecules. Then use the *Lock* button to make this orientation the *Home View*. In any case, you should now find that the mouse buttons translate and rotate both molecules in the scene.

You can now use the *Intermolecular Axis* (double headed arrow on the right border) to enable the display of the intermolecular axis. This axis connects the default centroids of each molecule. The *Origin Editing* button allows you to move these centroids and the *Orientation Editing* button allows you to rotate each molecule about its centroid and to translate each molecule relative to the scene. These operations are described in more detail in See Chapter 4 [Manoeuvring Molecules], page 16.

TIP: The *R slider* bar can be used to change the intermolecular separation permanently, as described above, but it is recommended that you use this control only for temporary changes to the scene (e.g. when viewing the result of docking or superposition calculations) and that you make permanent changes only in *editing* mode.

## 2.3 Keyboard Keys

All of the features in *Hex* are controlled using the GUI components. However, when you place the mouse in the main graphics window, several keyboard keys can be used as additional short-cut ways of controlling the program. For example, **F** toggles between full-screen and windowed mode, **G** toggles the GUI display in full-screen mode, **S** toggles stereographics on or off (if stereo is available), **P** toggles between perspective and orthographic projections, and **B** toggles a checker-board background (which can help enhance perspective projections). Hitting the escape key (**Esc**) or typing **Ctrl/Q** will exit the program. Rapidly typing **Ctrl/C** twice in the *terminal window* will abort *Hex* even if its in the middle of a calculation. However, such an *interrupt* may be ignored at certain times during a docking calculation on multi-CPU platforms. If you really want to kill a long running (or stuck) *Hex* job, type **hex -kill** in another terminal window. When viewing the calculated orientations from a docking run, the **Page/Up** and **Page/Down** keys may be used to scroll through the predicted orientations, and the **Home** and **End** keys may be used to jump to the initial (before docking) and last docked orientations, respectively.

## 3 Molecular Graphics

*Hex* can display protein and DNA molecules in several ways. The simplest display styles are controlled by the settings in the *Molecule Control* panel and some of the short-cut buttons on the right-hand border. Molecules can also be displayed as *solid models* (see Section 3.2 [Solid Models], page 8), *solid surfaces* (see Section 3.4 [Solid Surfaces], page 9), *spherical harmonic surfaces* (see Section 3.5 [Spherical Harmonic Surfaces], page 10), and *dot surfaces* (see Section 3.6 [Dot Surfaces], page 11 panel). These display types are controlled by additional control panels under the main *Graphics* menu. This menu also contains options to allow the foreground and background colours to be selected, the position and colour of a directional light to be modified, and a simple *Fog* effect to be applied.

### 3.1 Basic Display Styles

The basic appearance of protein and DNA molecules is controlled by the *Molecule Control* panel. The default style is to draw all covalent bonds as a skeleton, with each half-bond colour-coded by atom type. Probably the two most useful controls in this panel are the *Show Sidechains* toggle (which displays a protein in backbone-only or backbone+sidechain mode) and the *Colour Scheme* selector, which allows a limited degree of control over the colours used to draw each molecule. Line widths may be changed using the *Bond Widths* control.

When a protein or DNA molecule is loaded, *Hex* adds any missing polar hydrogen atoms using a set of templates from the **atom.templates.dat** file in the **data** directory. Polar hydrogens can be displayed using the *Show Hydrogens* toggle. The *Show Sidechains* toggle has an equivalent short-cut button on the right-hand border of the main window (which is supposed to look like a phenylalanine residue). Setting *Show Sidechains* to *off* (which also turns off hydrogen atom display) makes manipulating complex scenes easier.

When viewing large molecules, it's sometimes useful to draw only those atoms within a given distance of the molecular origin. The *Apply Radial Cutoff* button may be used to enable this behaviour, and the *Radial Cutoff* slider may be used to adjust the radial distance threshold. Distances are relative to the current scene rotation centre, which may be changed using *Origin Editing* button in the left-hand border (the crossed circle icon).

The *Colour Scheme* selector allows the molecular skeleton to be coloured from a fixed palette of colours or by using very simple commands in a text file to specify particular colours for specific residues. Some examples of colour files can be found in the **examples** directory. The general format for a colour file is:

```
chain first_residue last_residue colour_name
```

where **colour\_name** is any one of the X11 colour names. The colour names may be found by listing the **rgb.colours.dat** file in the **data** directory. Alternatively, each time a colour is picked from the *Colour Chart* its name is printed to the terminal window. Shown below is an example colour file **3hfl.col** from the **examples** directory, which specifies the colours to use when drawing an antibody/antigen complex. Subsets of the residues in each chain are assigned different colours to highlight the positions of the antibody hypervariable loops:

```
L 1 214 grey
L 25 33 red
```

```
L 90  97 blue

H 1   225 RoyalBlue1
H 25   33 red
H 52   56 yellow
H 95  102 green

Y 1   999 OrangeRed
Y 41   53 yellow
Y 67   70 red
Y 84   84 blue
```

Colour files may also be used to colour atoms explicitly, using the syntax:

```
atom_name    first_atom    last_atom    colour_name
```

More sophisticated colour selection schemes could be implemented, but visualisation issues get a rather low priority in *Hex*.

The *Molecule Control* panel also contains toggles to display *molecular centroids* and *average molecular ellipsoids*. The ellipsoids are calculated from low order (L=2) spherical harmonic surfaces. This control panel also allows the display of any crystallographically related molecules whose coordinates are not given explicitly in the PDB file. Use the *Symmetry Type* selector to select these additional symmetry elements. Selecting *Crystal* causes the scene to be generated using the SMTRY transformations from the PDB file, *Biological* selects the transformations from the BIOMT records, and *None* (the default) just uses the explicit atoms coordinates as usual. Note that atom coordinates are only replicated at display time using OpenGL display lists, so that even quite large molecules can be displayed reasonably quickly. A fun one to try is the tobacco mosaic virus (PDB code 1RMV), especially when low resolution harmonic surfaces are enabled. Another nice structure is the viral coat protein of the phi-X174 bacteriophage (PDB code 1CD3), which just happens to be the 10,000th entry in the PDB. By selecting the **File ... Save ... Symmetry ... Biological** option, *Hex* will write out all the symmetry-related atom coordinates when saving a structure to disc. This is useful in cases where the biologically active molecule is a dimer (or has some sort of symmetry) but only the minimal coordinate set appears in the PDB data file. Some further editing of the output file (e.g. to rename duplicated chains) may be required if the chains are to be individually coloured, for example.

## 3.2 Solid Models

The **Graphics ... Solid Models** control panel contains several options for drawing lit solid models of molecular scenes, including van der Waals spheres, licorice, and tube representations. Aromatic rings may be drawn as hexagonal or pentagonal “blocks”, which can produce some interesting displays, especially when viewing DNA molecules. The position and colour of the light may be controlled using the controls in the **Graphics ... Lighting** control panel.

### 3.3 Cartoons

The **Graphics ... Cartoons** control panel contains several options for drawing proteins as ribbon cartoons. The default behaviour is to draw a cartoon over the molecular skeleton. To view only the cartoon, you should disable the molecular skeleton using the *Display Molecule* button in the **Controls ... Molecule** panel.

The type of secondary structure within each protein chain is currently calculated using Frishman and Argos' **Stride** (<ftp://ftp.ebi.ac.uk/pub/software/unix/stride>) program.

### 3.4 Solid Surfaces

Solid molecular surfaces may be drawn using the **Graphics ... Solid Surfaces** control panel. These surfaces are calculated using a novel *marching tetragons* algorithm to contour a Gaussian density representation of the atoms of each molecule. The surface skins used in the docking correlations are calculated using this Gaussian density approach.

The *Colour Mode* selector allows surfaces to be coloured by atom colour (the default), electrostatic potential or charge density, or by using the “classic” blue-red colour scheme used in earlier versions of *Hex*. For electrostatic surfaces, a *colour ramp* is calculated which initially shows positive potentials/charges in blue, negative values in red, and intermediate values in white. The **Surfaces ... Colour Ramp** button may be used to activate a simple graphical controller for the colour ramp. The electrostatic potential and charge density displays are calculated from the *in vacuo* global charge density expansion using the current spherical polar docking expansion order, N.

The colours in a charge density display may appear somewhat “washed-out” compared to (perhaps more familiar) potential displays. This is because the potential is calculated directly from the charge density using Poisson's equation, and the del-squared form of this equation strongly emphasises any local variation in the charge density. So if the potentials “look right” then the charge density is also correct. NB. *Hex* uses a relative permittivity value of 8, instead of the more usual value of around 80. So, in addition to *Hex's in vacuo* assumption, the numerical values for the potential are likely to differ from other software.

Some molecules may have internal cavities, and these can produce one or more contour surfaces in addition to the primary external surface. Other molecular structures (e.g. structures with many waters, or well-separated domains) may also give multiple surfaces when contoured. As the contouring algorithm implicitly produces positively oriented surfaces (outward normals, positive total volumes), it is convenient to assign each calculated surface to one of two possible classes: *Primary* (positive volumes, outward normals), or *Secondary* (negative volumes, inward normals). By default, only *Primary* surfaces are displayed, but this may be changed using the *Draw Surface* control.

In addition to the default Gaussian surface, the *Surface Type* selector provides the option to draw contoured density functions of the *Sigma* and *Tau* surface functions as used by the docking algorithm. These two density functions allow the shape functions used in docking calculations to be visualised. *Sigma* is the external skin density function, typically calculated with a probe radius of 1.4Å, and *Tau* is the interior density function (effectively, the

van der Waals volume). For relatively small molecules, and when using high expansion orders ( $N$ ), the *Tau* density can be seen to give a remarkably good representation of the initial (atomic) Gaussian density. The order of the 3D expansion (default  $N=25$ ) is taken from the **Docking ... Final Search** parameter in the *Docking Control* panel. Both the *Sigma* and *Tau* surfaces are contoured using a hard-wired density value of 0.25. However, reconstructing each 3D density from the shape expansion coefficient vectors is a relatively expensive calculation. This display mode is mainly intended to illustrate the internal representations used in docking.

The *Sigma/Tau Shift* slider controls how the shape (and electrostatic) expansion coefficients are computationally translated using the  $T(R)$  translation matrices prior to reconstructing the surface from translated expansion coefficients. Thus it is possible to view graphically how the representation used in the docking correlation degrades with increasing distance from the origin. In this display mode, the receptor surface is translated in the negative  $z$  direction, and the ligand surface is translated in positive  $z$  for ease of viewing. You should see a blurring of those portions of each molecule furthest from the origin, although the shapes of the surface regions near the origin are very well preserved after translation. NB. In *Hex*'s docking correlations, all computational translations are applied entirely to the receptor.

Be aware that drawing surfaces can use a lot of memory. Drawing the surface of a large molecule using a fine (0.25-0.5 Ångstrom) grid can use *hundreds of megabytes of memory*. Attempting to draw a complex surface on a machine with insufficient memory could cause the machine to hang.

### 3.5 Spherical Harmonic Surfaces

The *Harmonic Surface* control panel controls the way in which spherical harmonic molecular surfaces are calculated and displayed. Spherical harmonic molecular surfaces are generated from the dot surfaces calculated by *Hex*'s internal dot surface algorithm, according to the parameters set in the *Harmonic Surface* control panel. These parameters are distinct from similar parameters in the *Dot Surfaces* control panel which generates dot surfaces purely for visualisation (see Section 3.6 [Dot Surfaces], page 11).

When *Hex* calculates a spherical harmonic molecular surface, it first finds the shape of an *angular envelope* which just enclosed all dots of the dot surface. This envelope is made up of a list of approximately evenly spaced angular sample points (derived from the vertices of a *tessellated icosahedron*), along with a radial distance from the origin to the surface at the corresponding angular sample. Note that the surface envelope does not properly handle multi-valued, or *re-entrant*, surfaces. That is, if a ray from the origin cuts the molecular surface more than once, only the most extreme cut point is recorded for the given angular sample. Nonetheless, this type of global envelope often gives a remarkably good low resolution representation of most protein surfaces.

By default, the molecular envelope just described is not normally displayed. Instead, *Hex* uses the sample points of the envelope to calculate a parametric representation of the envelope using a spherical harmonic power series expansion. You can view the molecular envelope by selecting:

Graphics ... Harmonic Surface ... Enable Surface (toggle on)

The sampling resolution is controlled by the *Dot Density* selector and the *Mesh Order* slider. The dot density is the number of dots originally assigned to each atom in the dot surface calculation. The mesh order controls the number of vertices in the icosahedral angular mesh by defining the number of subdivisions along each edge in the original icosahedron. The *Probe Radius* slider may be used to modify the size of the probe sphere used in the initial dot surface calculation. Setting a probe radius of zero would give a van der Waals surface, instead of the molecular surface. The envelope may be displayed in different styles and colours using the *Display Mode* and *Line Colours* selectors. By disabling the envelope display and by enabling spherical harmonics, one can view the corresponding spherical harmonic molecular surface:

```
Graphics ... Harmonic Surface ... Enable Surface (toggle off)
Controls ... Harmonics ... Enable Harmonics      (toggle on)
```

In fact, these are *Hex*'s default settings, so that once a molecule has been loaded, pressing the *Harmonics* button on the right hand border calculates and displays a spherical harmonic surface directly. The *order* of the spherical harmonic expansion can be selected using the *Order (L)* slider in the *Harmonics Control* panel.

### 3.6 Dot Surfaces

These days, dot surfaces are somewhat of a historical remnant in *Hex*. They used to be used as an approximate but fast way to calculate the *molecular surface*, the *solvent-accessible surface* and the *van der Waals surface* for docking. However, docking and superposition calculations now use a much more accurate method based on contouring Gaussian density functions to calculate these two surfaces. Nonetheless, its still sometimes useful to be able to draw dot surfaces. If nothing else, dot surfaces give a fast way to verify that *Hex* is recognising all the atoms in a PDB file because sometimes unrecognised atoms may not be drawn in the other drawing modes, whereas the dot surface calculation always uses *all* atoms, regardless of their type. Spherical harmonic surface envelopes are also calculated from the sampled dot surface.

The calculation and display of dot surfaces is controlled by settings in the *Dot Surface* control panel. The short-cut *Dots* button on the right-hand border of the main window provides a fast way to toggle the display of dot surfaces. By default, *Hex* displays a *molecular* surface calculated using a 1.4 Ångstrom radius probe sphere.

Dot surfaces are calculated by covering the surface of each atom with a set of sample points generated from an icosahedral tessellation of the sphere. The default dot density is 162 dots/atom, but this may be changed using the *Dot Density* selector. Any dots which are occluded by neighbouring atoms are immediately discarded. If the *Probe Radius* is zero, then this gives the van der Waals surface. Otherwise, the program calculates the molecular surface and solvent-accessible surface by rolling a probe sphere over the surface (non-occluded) atoms of the molecule.

When *Hex* calculates a molecular surface, non-occluded atom dots are classified as one of *convex-accessible*, *toroidal-reentrant* or *singular-reentrant*. These classifications correspond to the type of contact the dot should make with a probe sphere being rolled over the molecule. The *convex-accessible* dots are those which may be touched by the probe when the probe sphere is not simultaneously in contact with any other atom. All other dots

are considered as *reentrant*. Reentrant dots are then “pushed out” from the atom surface to meet the locus of the molecular surface. The position of the reentrant surface can be calculated by a 2D analysis of the path of the probe sphere for *toroidal* dots and by a similar calculation using the 3D stationary probe positions for the *singular* points (when the probe simultaneously touches 3 or more atoms). Without going into more detail here, the algorithm is *exact* when an infinitely small probe is used but the quality of the resulting surface degrades as the probe size increases. This is because there is only a fixed number of dots with which to populate the re-entrant surface regions. However, this degradation is hardly noticeable with probe radii up to about 1.5 Ångstroms. Since the dot surfaces produced here are primarily for computational rather than visualisation purposes, a modest degree of inaccuracy is quite acceptable.

The type of dot surface which is actually displayed is controlled by the *Skin Factor* slider. Setting the skin factor to zero causes the molecular surface to be displayed: a skin factor of one draws the solvent-accessible surface. Intermediate values cause dots to be drawn at the corresponding fraction along each of the outward surface normals. The *Display Mode* may be changed from *dots* to *vectors*, in which case surface normals are drawn as lines of the length implied by the current skin factor. Vectors are drawn as dots if the skin factor is zero. Dots (or vectors) may be coloured according to atom type or a colour may be selected from the colour chart using the *Dot Colours* selector.

### 3.7 Changing The Scene Origin

Normally, rotation and scale (zoom) operations are applied relative to the scene origin. When just one molecule is loaded, the scene origin coincides with the centroid of the molecule. However, when two molecules are loaded, the scene origin is taken as the midpoint between the two molecular centroids. This behaviour can be changed by using the first selector in the *Orientation Control* panel to select a given molecular centroid or a specific atom to act as the origin. The *Select Origin* button (a circle with a diagonal cross through it) on the left hand border may also be used to select the zoom/rotation centre.

Although docking calculations normally move both the ligand and the receptor, the default display behaviour is to keep the receptor fixed in space and to assign all the motion to the ligand as successive docking solutions are viewed. This behaviour can be changed using the *Docking Motion* selector in the *Orientation Control* panel.

### 3.8 Clipping The Scene

The *Clipping* button (three faces of a cube) on the left hand border selects *scene clipping* mode. You can define up to six clipping planes in the scene, several of which may be moved together using a single slider. However, controlling clipping is probably the most difficult part of the program to master, since this involves the use of all three mouse buttons and several keyboard keys, in addition to the basic graphical widgets.

When scene clipping mode is selected, you should see a wire frame drawing of six skeletal clipping planes centred in the scene. A new slider control is also drawn in the bottom right border. This new slider may be used to move selected clipping planes through the scene, in plane-perpendicular directions.



In clipping mode, the mouse buttons may be used to translate and rotate the clipping skeleton in the usual way. Note however, that the rest of the scene remains fixed. You can use the keyboard **Space Bar** to toggle between moving the skeleton about the scene and moving the scene about the skeleton.

Picking one of the skeletal planes (using **Button 1** for picking) *selects* that plane and *attaches* it to the scene. The plane is now drawn in white, either as a filled shape or as an outline, depending on which face you happen to be viewing. The mouse buttons now move only this plane relative to the scene (or, if you have hit the **Space Bar**, the mouse moves the plane and the scene together). The filled face will become the clipping face of that plane.

**Button 2** may be used to *activate* the selected plane (just press **Button 2** anywhere in the scene). That is, every part of the scene above the filled face should become clipped. Pressing **Button 2** again toggles clipping. Try moving the clipping plane through the scene using the right slider, or by using the mouse and the **Space Bar** to control the movement. Try using the **Delete Key** (keyboard backspace) to toggle the sense of the clipping plane. Once you are happy with the position of the clipping plane, you can revert to *Pointer Mode* (select the *Left Arrow* button) or you can proceed to pick and activate further clipping planes. In pointer mode, the right hand slider continues to operate the most recently activated clipping plane.

It is also possible to make the slider move two planes simultaneously. Having activated a clipping plane, now try picking it with **Button 3**. This draws the plane in yellow and ties its motion to the slider. Now pick and activate the clipping plane (using Buttons 1 and 2) on the opposite face of the clipping skeleton. The right slider should now move both planes together through the scene. You can tie multiple planes to the slider, although selecting two perpendicular planes is probably the most sensible option. As you might expect, picking a plane with **Button 3** for a second time unties it from the slider.

At any time while in clipping mode, you can undo the most recent operation using the *Hammer* button. Three successive clicks on the *Hammer* will clear all clipping settings and will return the display to an unclipped scene.

If necessary, you can use the keyboard **Plus** and **Minus** keys to zoom the clipping skeleton independently of the scene. If the scene contains molecular surfaces (dots, lines or polygons), you can use the keyboard **Equals** key to toggle between clipping both the molecule and its surface (the default) and clipping just the surface, leaving the molecular skeleton fully visible.

## 3.9 Animation

The *Animation Control* panel allows you to run a “movie” of either the results of a docking calculation, or a sequence of models from an NMR structure, for example, and it controls how the scene “spins” if you perform a mouse drag-release action.

After a docking run, pressing *Start* in the **Graphics ... Animation** control panel will cause *Hex* to draw each docking solution in turn. The rate at which orientations are drawn is controlled by the *Frame Rate* slider. Similarly, if you have loaded a PDB file that contains several NMR model structures, setting the *Movie Type* to *Receptor Models* or *Ligand Models*, as appropriate, and pressing *Start* will show a movie of the sequence of models. The orientations, or frames, of both types of movie may be shown just once, or cycled forever.

The movie can be stopped at the current frame by pressing the *Stop* button. The speed of the movie is controlled by the *Frame Rate* slider.

The maximum frame rate achievable will depend on the speed of the CPU and on whether your machine has hardware-accelerated graphics. The *Frame Rate* thus defines a requested rate. Actual performance will vary. But please note, *Hex* never hogs the CPU in a tight loop on input events, even during an animation, as do many other programs (which shall remain nameless). Thus it should still be possible to perform other activities while a movie is running without things becoming sluggish.

You can *spin* the scene by dragging with **Button 1** or **Button 2** to start a rotation and by releasing the button while still moving the mouse to initiate a continuous rotation (spinning). When spinning, the rotation angle is incremented by the current value in the *Spin Angle* slider, and new rotational increments are drawn at the current *Frame Rate*. If desired, the mouse button action that initiates spinning can be enabled/disabled with the *Enable Spinning* toggle. Spinning is enabled by default, and it is possible to spin a movie (if that's what you really want to see!).

Any of the usual user interface controls may be used while an animation is running. If using these controls changes the graphical complexity of the scene, *Hex* will take a second or two to adjust the drawing speed back to the requested frame rate.

### 3.10 Full Screen Mode

Personally, I think full-screen mode is the best way to view molecular graphics scenes. You can press **F** to switch back and forth between full-screen and window-manager modes. By default, *Hex* starts in window-manager mode. You can also press **G** at any time to toggle the display of the GUI controls when in full-screen mode. **G** only toggles the setting, not the display. So you won't see the effect until you enter full-screen mode.

In both the Unix and Windows versions, you should always use **F** to get full-screen mode because this forces the window border off. Conversely, don't use the window manager's "maximise" control because this forces the window to keep a border, and **F** won't then work.

On Windows XP, you will probably still see the Windows Taskbar in full-screen mode. To get rid of this, open the **Taskbar and Start Menu** in the *Windows XP Control Panel* and uncheck the *Keep the taskbar on top of other windows* item. I don't know whether this feature is available on earlier versions of Windows.

On Linux (RedHat 9), full-screen GUI mode with the Gnome window manager is "quirky". Everything works as above, except that *Hex* control panels can't be re-raised over the full-screen window after the control panel loses mouse focus (i.e. when the cursor leaves the panel). You will need to revert to window-manager mode (**F**) to see everything again! I don't know what other Linux window managers might do, but it seems many window managers don't handle full-screen windows very well!

### 3.11 Stereo Displays

Stereographic displays should work on systems that support "stereo-in-a-window" (untested on SGI and Sun). Stereo is known to work on Windows XP and RedHat Linux

8.0 (kernel version 2.4.18-14, XFree86 version 4.0.0) or later with an nVidia Quadro4 XGL700 card, and using a recent nVidia driver (1.0.3123 or later).

For best results with *Hex* and nVidia cards, please use the latest versions of both driver software, service packs, and operating systems. The recent nVidia drivers give *Hex* both stereo-in-a-window and full-screen stereo on both Windows XP and Linux. nVidia's 4351 driver (May 2003) is excellent, and is very easy to install. See Appendix D [nVidia Stereo Configuration], page 48 for more details. However, if you are upgrading an nVidia driver on Windows, **ensure you de-install any earlier drivers first**. I caused myself significant grief by not doing this!

However, for reasons I still don't understand, the Linux version of *Hex* still gives a SIGSEGV fault when first starting up with an nVidia graphics card (as does the 4191 driver, December 2002), but it starts OK on subsequent attempts. [Technical note: I'm not sure, but this seems to be related to the first call to `XCreatePixmap` to make the buttons for the GUI borders (the actual fault happens in `XGContextFromGC`, and is trapped by `_dlopen`). What's this got to do with nVidia? I don't know, but it doesn't happen with the Mesa OpenGL driver.] I hope this will be resolved in future driver versions.

The type of graphics visual that *Hex* uses is determined when the program first starts up. By default, *Hex* tries to use a stereographics window. However, this nearly halves the drawing rate compared to non-stereo drawing. So if you don't like/want stereo, you can force stereo off by using `hex -nostereo`. Alternatively, set the `HEX_STEREO` environment variable to a false value (i.e. any one of: no, n, false, f, or 0) in your login script. If a stereo visual has been selected, the display may be toggled between stereo and mono using the *Stereo Parallax* option in the *Projection Control* panel (or simply by pressing the keyboard S key). The *Parallax* slider may be used to adjust the stereographic effect. Stereo parallax is the perceived separation between the left and right images in the viewing plane (monitor screen). The numerical values in the parallax slider correspond approximately to screen millimetres on an un-zoomed display. Positive parallax values make the scene appear "inside" the display, whereas negative values cause the scene to appear through, or in front of, the plane of the display. A better stereographic effect is achieved when the *Perspective Projection* toggle is enabled (by default, an orthographic projection is used). The keyboard P key may also be used to toggle between perspective and orthographic projection modes. When perspective is enabled, a checker-board background may also be enabled to enhance the perspective effect (keyboard B). The perspective effect can be increased by reducing the *Far Plane* and/or increasing the *Near Plane* slider values. For most people, a small positive parallax and a moderate perspective gives a pleasing effect without straining the eyes.

For PC/Linux stereo, you should download the *shared-link* executable (see Section 6.10 [Technical Information], page 36) because hardware stereo support is currently only available in the vendor-supplied GL/GLX libraries. Even if you don't have hardware stereo, you may still get better graphics performance using the *shared-link* executable if your graphics card has hardware-accelerated OpenGL support.

## 4 Manoeuvring Molecules

In addition to rotating, translating, and scaling a molecular graphics scene, *Hex*, also allows you to change the *relative* orientations of a pair of molecules. *Hex* calls this *editing*, because saving “manoeuvred” structures out to a file causes them to be written using their transformed coordinates. Note: *Edit Mode* is only enabled when you have two molecules loaded. *Editing* is often a necessary preparatory step before running a docking calculation. For example, when you load a pair of molecules, *Hex* uses some heuristics to place the ligand near the receptor. However, you may have knowledge about one or both of the binding sites, and hence you may want to manoeuvre the molecules into something that approximates the expected binding orientation. If you do this, you can then limit the search range of the docking correlation instead of performing a global search. This should give fewer “false-positives”, and it will certainly make the docking calculation go faster.

**TIP:** In the graphics, you can edit both the receptor and the ligand orientations, but the coordinates of the receptor “take priority” when structures are saved to disc. In other words, any relative motion is *always* transferred entirely onto the ligand on output. The receptor coordinates are always restored to their original values.

### 4.1 Editing Orientations

There are two main ways to edit molecular orientations within the scene. In the first method, using the *Orientation Control* panel, a molecule may selected using the *Apply to* selector and then rotated using the Euler angle *Alpha*, *Beta* and *Gamma* sliders. The inter-molecular separation can be modified with the *R slider* at the bottom of the main window. Select *Commit* when you’re done editing, in order to commit the new transformations into the molecules. In the second method, editing can be performed by manually manipulating the scene with the mouse by pressing the *Edit Mode* button (which looks like a lightning bolt) in the left border. This method can also be used in conjunction with the *Orientation Control* panel.

In both editing modes, *picking* a molecule ties its motion to the mouse and to the rotation sliders in the *Orientation Control* panel. The bonds of the picked molecule are displayed as dashed lines as a visual reminder that this molecule has been activated for editing. Picking the background (i.e. a **Button 1** pick that misses all atoms) de-selects the active molecule and makes the mouse move the whole scene. The *Hammer* button can be used to undo the most recent sequence of editing movements. When editing molecular orientations, it may help to activate the *Intermolecular Axis*. Once you’re happy with your edits, revert to *Pointer Mode* to commit the new orientations. You can now save the scene by going to the *File* menu and selecting:

**File ... Save ... Both**

This causes a file selection widget to appear, prompting you for the name of a file in which to save both molecules (in the newly edited orientation). You can confirm the new orientation has been created by loading the new file into another *Hex* session (you may have to rotate the scene to see exactly the same view). Alternatively, you could write each molecule to a separate file using:

File ... Save ... Receptor  
and

File ... Save ... Ligand

You could then open these new files to verify the new orientation.

You may want to try using these editing features to manually dock the ligand into the receptor binding site (if appropriate), or you might try to superpose the two molecules, if they are similar. Neither task is easy!!

## 4.2 Editing Centroids

When *Hex* reads in a molecule, it uses its all-atom centre of mass as its centroid. This centroid is used as the local coordinate origin for docking, and as the point about which any molecular rotations are applied. However, if one or both molecules are quite large (i.e. too big to fit within about a 30 Ångstrom radius ball), you will probably want to change the centroids used for docking. This is because *Hex*'s radial functions fall off rapidly beyond about 30Å from the origin. *Hence, unless you move the origin(s) to be closer to the expected binding site(s), you are likely to get very poor docking results.* If you don't know or suspect where the binding site is on a large molecule, you should use *Hex*'s *macro docking* mode for such cases. See Section 5.10 [Macro Docking], page 24.

Molecular centroids may be edited using the *Edit Origins* button (two crosses and a line) on the left-hand border. Try changing to *Edit Origins* mode, and pick a molecule to edit. Once the picked molecule is highlighted, dragging **Button 1** will move the origin of the selected molecule. As with editing orientations (above), it may help to activate the *Intermolecular Axis* in order to see the new and old positions of the centroid(s). In *Edit Origins* mode, buttons 2 and 3 always rotate the entire scene. When you revert to the default *Pointer Mode*, the new origin will be activated. Note that the new origin only applies to the current session. It is not saved when you write an edited molecule to disc.

**TIP:** You can use virtually all of the other GUI functions while in edit mode, although certain operations (e.g. opening/closing molecules) cause *Hex* to revert to pointer mode.

## 5 Docking Molecules

In order to run a docking calculation in *Hex*, you will need to load a *receptor* and a *ligand* PDB structure using the *File* pull-down menu. If you want to test the docking algorithm by docking two separately determined sub-units of a complex for which the crystal structure is also available, you can also load the *complex* structure which will be used as a *reference orientation* to evaluate the accuracy of the docking prediction.

Generally, you will have to remove water molecules and any other *hetero* molecules prior to docking. You can do this globally using the *Hetero Control* menu panel. If more detailed control is required, you will probably have to edit each PDB file manually. It may also be necessary to remove other chains in the PDB file or to shorten a chain to the domain of interest in docking. For example, when docking an antigen to an antibody it is usually advisable to delete all but the Fv fragment of the antibody structure (although the program has been used to dock a protein G molecule to a complete Fab fragment). Having edited your PDB files, you should have a *receptor* and a *ligand* file which contain only the receptor and ligand molecules, respectively, and (optionally) a *complex* file, which contains both molecules in the docked orientation. When using a *complex* structure, you should ensure that the chain names are consistent with those of the *receptor* and *ligand* because *Hex* uses the chain labels to identify and hence superpose corresponding pairs of alpha-carbon atoms from each chain in order to calculate RMS deviations between the docked position of the ligand and its position in the known complex.

**TIP:** You can use the utility **hex\_chain** in *Hex*'s **bin** directory to rename a chain in a PDB file.

Up to three protein structures can be loaded into *Hex* directly from the command line. For example, to load three of the PDB files from the **examples** directory for the HyHel-5/lysozyme complex, you could type at the Unix prompt:

```
hex 3hfl_fv.pdb 3hfl_ly.pdb 3hfl.pdb
```

However, its often more convenient to load all three molecules together using a short macro file, similar to those in the **examples** directory. For example, the macro file, **3hfl.mac**, can be executed by selecting:

```
Macros ... Run ... 3hfl.mac
```

This macro file contains the following:

```
#
# 3hfl.mac
# =====
#
# This example macro file loads the antibody HyHel-5/lysozyme complex.
# By default, Hex will look in the $HEX_ROOT/examples directory
# for the PDB files and the colour file referenced here. You may wish
# to change this behaviour by setting some environment variables in
# your .login (csh) or .profile (sh/ksh) files.
#
close_all
set_colour_file 3hfl.col
```

```
open_receptor    3hfl_fv.pdb
open_ligand      3hfl_ly.pdb
open_complex     3hfl.pdb
fit_ligand
```

When using a *complex* reference structure, you should find that on loading the molecules, the complex is drawn in grey and the receptor molecule is superposed onto the appropriate part of the complex. If the ligand molecule originated from an edited *complex* file, then it will be superposed over the complex (because its coordinates are relative to the same coordinate frame as the receptor molecule). Otherwise, the ligand can be transformed into the receptor/complex frame using the *Fit Ligand* button in the *Orientation Control* panel.

## 5.1 Rotational Search

*Hex* currently supports *three* docking search modes, which may be selected using the *Search Mode* selection box in the *Docking Control* panel. Most docking problems require only the default *Full Rotation* mode, in which the receptor and ligand are effectively rotated about their own centroids, and the ligand is twisted about the intermolecular axis at each of a range of intermolecular distances. Thus the default behaviour is to perform a full six-dimensional search over the full rotational ranges. However, more limited docking searches can be performed in which the allowed angular and distance ranges may be constrained by the user. The calculation is arranged so that the intermolecular twist angle search is in the innermost loop of the algorithm. This innermost loop turns out to involve a sum over sines and cosines of the twist angle, which may be accelerated using a one-dimensional FFT.

There are several controls which specify the resolution, and in particular the *order*, *N*, of the docking correlation. The default settings are for the program to perform an initial *Steric Scan* at *N*=16, followed by a *Final Search* at *N*=25, using just the steric contribution to the docking energy. In this mode, about all but the top 20,000 orientations are discarded after the *Steric Scan*. The *Steric Scan* may be toggled off, in which case every orientation is evaluated using a steric correlation (and optionally an electrostatic correlation) to order *N*, as given the *Final Search* slider. However, this can significantly increase total docking times. Using the two-step search with *N*=16 and *N*=25 is found to work well in practically all cases. The electrostatic contribution to the docking correlation may be enabled using the *Electrostatics* toggle. Electrostatics are only ever calculated in the *Final Search* phase. You can get a feeling for how well each correlation order, *N*, recognises a given complex by running the program on known complexes and by observing how highly the correct solution is ranked in each case.

NB. Although the default is to use correlations to *N*=25, in the recent **CAPRI blind trial** (<http://capri.ebi.ac.uk/>), I found that better results are obtained using *N*=30 correlations (see Section 6.14 [References], page 37).

## 5.2 Other Search Modes

In addition to the basic rotational search, *Hex* also supports a *Ligand Translation* and a *Ligand Orbit* search mode. In *Ligand Translation* mode, the receptor is held fixed and the ligand is translated about the receptor using the *Ligand Range* and *Samples* angular

parameters and the *Distance Range* and *Step* parameters to generate different ligand poses about the receptor. A pure translation is achieved if the *twist angle* is set to zero.

In *Ligand Orbit* mode, the ligand is translated as above, but it is now also rotated about its own principle axis (in fixed steps of 10 degrees). A “wobble” may be added to the search by setting a small range (say 30 degrees) for the *twist angle*. These search modes are largely experimental, but may be useful if the relative orientation of a pair of molecules in a complex is known but the exact binding mode is not.

These modes are less efficient than the default rotational search mode since they can’t exploit the fast (FFT) twist angle search on the innermost loop of a rotational docking search. If in doubt, use the default *Full Rotational* search mode.

## 5.3 Radial Filters

When performing a full 6D docking search, the most expensive part of the calculation is normally the initial steric scan. This phase can be accelerated by selecting a *Radial Envelope Filter* in order to avoid scanning orientations in which the molecules overlap significantly, or are too far apart for their surfaces to interact. There are two radial filtering modes, which both use low resolution spherical harmonic surface envelopes to define an approximate radial envelope for each molecule. The surfaces are constructed using the current expansion order (default L=12) from the **Controls ... Harmonics ... Order** selector. The *Re-entrant* filter assumes each molecule is fully contained within the harmonic surface, and excludes trial distances at which the surfaces are too far apart. The more aggressive *Star-like* filter assumes the surfaces are single-valued with respect to a ray from the origin, and additionally excludes trial distances at which the surfaces are presumed to be too close together for docking to be feasible. It is unwise to use these filters if either docking partner is non-globular.

## 5.4 Docking Examples

OK, lets start docking. Call up the *Docking Control* panel and select the following values from the selection boxes:

```
Controls ... Docking ... Receptor Range ...    30
Controls ... Docking ... Ligand Range ...      30
Controls ... Docking ... Receptor Samples ...  492
Controls ... Docking ... Ligand Samples ...    492
Controls ... Docking ... Twist Range ...       360
Controls ... Docking ... Twist Samples ...     128
Controls ... Docking ... Distance Range ...    31
Controls ... Docking ... Distance Step ...     0.75
```

This says that the docking calculation will be performed at  $31/0.75=41$  intermolecular separations (starting from the current distance posted in the *R* slider in the bottom border of the main window), and that the angular search will be restricted to 30 degree angular cones centred on the intermolecular axis. Now start the calculation:

```
Controls ... Docking ... Activate
```

You’ve just started an example docking search restricted to the known binding sites, so the calculation should only take a few minutes. The program will take a few seconds to calculate



the surface skin coefficients and then proceed to calculate docking correlation scores at each of the specified angular and intermolecular increments. A Cartesian grid is used to sample the molecular skins numerically but this grid plays no further role in the calculation once the surface skin expansion coefficients have been determined. Most conventional FFT docking algorithms have to use rather large grids (e.g. 1 Ångstrom cubes) because the grid must accommodate all possible translations of the ligand about a stationary receptor. Here, the grid only needs to contain the larger of the two molecules so that much finer grids are feasible. In *Hex*, a 0.6 Ångstrom grid seems to work well and is still reasonably fast to calculate. The sampling grid size may be varied using the *Grid Dimension* selection box. The calculation of the surface skins used in the docking correlation is controlled by the parameters in the *Surface Control* panel. The default values do not normally need to be changed.

The search in the above example is “restricted” because setting the ligand and receptor *range angles* to 30 degrees means that only a small fraction of the 492 rotational increments (the *Receptor Samples* and *Ligand Samples* values) will actually be used for the *molecular rotations* of each molecule. These rotational samples are generated from an icosahedral tessellation of the sphere and, in this case, have an angular separation of about 10 degrees between each sample point. Essentially, each molecule is rotated incrementally so that successive tessellation points are rotated onto the intermolecular axis (the *z*-axis). Thus, in the low resolution *Steric Scan* phase, 492 x 492 distinct rotational orientations are produced, although any orientations that fall outside the angular range cones are discarded. At each of the surviving orientations, the ligand is then rotated (or *twisted*) through 360 degrees about the *z*-axis in 64 steps of about 5.6 degree increments specified by the *Twist Samples* value. In this constrained example, *Hex* will evaluate the docking score at each of 31 x 31 x 64 = 61,504 distinct rotational orientations, with the calculation being repeated at each of the 41 (31/0.75) intermolecular distances implied by the distance range and step parameters (in +/- steps from the starting orientation). In the high resolution *Final Search* phase, the best 20,000 of the above orientations will be re-evaluated at N=25 using 128 samples for each twist angle search. Note, *Hex* is hard-wired to use 64 twist steps in the initial steric scan phase, because there no benefit in using finer steps in this phase.

It should be noted that such docking calculations never give a unique solution. Rather, *Hex* sorts the generated orientations by docking energy and prints a summary of the 10,000 highest scoring (lowest energy) orientations. The best 512 orientations are retained for viewing. You can view the solutions using the *Soln:* slider, or you can step through the solutions using the keypad keys:

```

Home:      Starting orientation
Page/Down: Next solution
Page/Up:   Previous solution
End:       512'th (or last) solution

```

You should find in the above example that *Hex* generates several orientations with low RMS deviations from the correct (starting) orientation. However, you might object that the calculation was biased to find the right answer by restricting the search to the known binding sites. If so, you could try a global docking search (say,  $6.3 \times 10^8$  orientations), using:

```

Controls ... Docking ... Receptor Range ... 180
Controls ... Docking ... Ligand Range ... 180
Controls ... Docking ... Receptor Samples ... 492

```

```

Controls ... Docking ... Ligand Samples ... 492
Controls ... Docking ... Distance Range ... 31
Controls ... Docking ... Distance Step ... 0.75

```

This calculation will take about 2 hours on a single R5000 CPU, or about half an hour on a 1GHz Pentium III. Such timings are substantially faster than an equivalent calculation using a conventional FFT approach. In this particular case, *Hex* should still identify the correct docking orientation (to within about 1.5 Ångstrom RMS), but its often useful to use restricted searches when starting with unbound subunits.

TIP: When viewing docking solutions, its helpful to keep either the receptor or the ligand in a fixed orientation in the display, so that only one molecule moves when stepping through the docking solutions. The default is to transfer any receptor motion onto the ligand, so that the ligand appears to translate and rotate about a fixed receptor. This behaviour can be changed using the *Orientation Control* panel:

```
Controls ... Orientation ... Centre ... Ligand
```

TIP: If you plan to use *Hex* more than once, enabling a *disc cache* will speed up the translational part of each calculation. When disc caching is enabled the (large) translation matrices are calculated only when necessary and are saved in the cache directory for re-use. Disc caching controls can be found under the *File* menu. The default cache directory is **\$HEX\_ROOT/cache**, although it is recommended to set a cache directory explicitly using the HEX\_CACHE environment variable. The cache directory should be specially created for this purpose (i.e. it contains nothing else) and a distinct directory should be used by each user (because there's no synchronisation between multiple invocations of *Hex*). With typical usage, the disc cache will occupy from 50 to 200 Mb of disc space.

## 5.5 Calculating Bumps

Following the basic docking correlation algorithm, candidate docking orientations may be filtered and refined using one of the *Post Processing* options. Post processing is applied to the top-scoring 1,000 solutions from the correlation search. The simplest option is to enable a *bumps* counter, in which the number of steric clashes between non-bonded pairs of heavy atoms in each solution is calculated. An option in the *Clustering Control* panel may then be used to filter out solutions with a specified number of steric clashes.

## 5.6 Molecular Mechanics Refinement

In addition to the bumps counter, a single (rigid body) molecular mechanics energy may be calculated for each docking solution (*MM Energies*), or a Newton-like energy minimisation (*MM Minimisation*) can be applied to each docking solution. These energies are calculated using “soft” Lennard-Jones and hydrogen bond potentials, adapted from the OPLS force-field parameters, along with an explicit charge-charge electrostatic contribution. When docking complexes where conformational changes are known to be small, this gives an effective way to prune many “false-positive” orientations and to enhance the energy of the “right answer”. However, this rigid-body refinement procedure should not be used if

conformational changes are expected to be large because (despite using soft potentials) it tends to eject ligands with incorrect conformations from the binding site. This part of the program is very much “under development”.

## 5.7 Clustering Docking Results

As *Hex* uses essentially a brute-force search approach to the docking problem, it is advisable to *over-sample* the search space rather than to risk missing a good solution by under-sampling the space. However, this can cause multiple similar but incorrect orientations (false-positives) to push good solutions down the list. By default, *Hex* uses a simple clustering algorithm to group spatially similar docking orientations. Each docking solution is first ordered by energy, and the lowest energy solution is made the seed orientation for the first cluster. The list is then searched for other similar orientations whose main-chain alpha-Carbon RMS deviation is within a given threshold (default 2 Å RMS) of the seed orientation, and these orientations are then assigned to the first cluster. The process is then repeated starting from the next lowest unassigned orientation, until all solutions have been assigned to a cluster.

The **Controls ... Clustering** control panel may be used to control the type of clustering and clustering parameters used, and how cluster membership affects the displayed solutions. By default, only the lowest energy member of each cluster is displayed or written to an output PDB file (*Display Clusters = Best*). Alternatively, you can choose to view (or output) all solutions (*Display Clusters = All*). Similarly, solutions may be viewed in cluster order (best to worst) or in order of calculated energy using the *Sort Solutions* selection option. The RMS threshold for cluster membership may be changed using the *RMS Threshold* slider. Displayed solutions may also be selected by the number of steric clashes, or bumps, detected. Any solution containing a number of bumps which is less than or equal to the current *Bumps Threshold* (default 0) is a candidate for cluster membership. Solutions with a greater number of bumps may still be viewed or output, but these always appear after any non-bumping solutions in the sorted list of solutions (i.e. have a larger cluster rank).

The default docking search range and clustering parameters are normally sufficient to generate good coverage of the search space, and to distinguish different but similar solutions. But you may wish to experiment. Clustering is re-calculated whenever a clustering parameter is changed, without having to re-run the docking search. Here, “good coverage” means that for each docking orientation, there is about a 99% chance of generating at least one other solution within 3 Å RMS of the first one (unpublished experiments). Deciding whether or not two similar but different orientations ought to fall within the same cluster is somewhat subjective. The 2 Å threshold seems to work well for large-ish ligands (roughly 100 residues), but should probably be reduced for smaller ligands.

## 5.8 Saving Docking Results

There are currently two ways in which docking results may be saved to disc. The most compact method is to write a *docking summary file* using the **File ... Save ... Docking** menu item. This writes a file that lists the docking energies for all predicted orientations, along with 3D transformation matrices which may be applied to the coordinates in the

original PDB files to produce the corresponding orientation. For rigid body docking, this is a compact output format, but you will need to write your own code to process the docking summary file. The second, less compact method, is to write a separate PDB file for each docking orientation. The current docking orientation can be written to a single PDB file by selecting:

File ... Save ... Both

Alternatively, a range of docking solutions may be saved using:

File ... Save ... Range

This opens a new *Save Docking Range* panel in which a range of docking solutions may be specified, along with a file name pattern to be used for the output files. The default is to save the first 100 solutions to separate PDB files of the form **dock001.pdb**, etc., in the current directory.

In both the PDB range and the summary output modes, either a list of *raw solutions* (sorted by energy) are written, or a range of clustered orientations are written, depending on the current clustering option. In other words, the sequence of solutions written out is the same sequence that you would see when stepping through the orientations using the Page/Down and Page/Up keys.

## 5.9 Docking Multiple Structures

Docking multiple structures (e.g. NMR structures) with *Hex* is easy. Just put all your ligand structures (assumed to be in a common coordinate frame) into a single PDB file, and use the PDB convention of MODEL/ENDMDL to distinguish each structure. *Hex* will run its docking search for each ligand in turn. Similarly, multiple receptor model structures may be loaded and docked, giving an *M by N* docking (may take a while though!). The actual structures to be docked may be selected using the *Receptor Docking* and *Ligand Docking* selectors in the **Controls ... Solid Models** control panel (default all v's all). Individual structures may be selected for viewing using the *Receptor Display* and *Ligand Display* selectors in the same control panel. This panel also contains some experimental controls for *cloning* and *editing* different models (where each clone is treated as a new NMR-type model structure to be docked, with each docking run each starting from the edited pose).

## 5.10 Docking Very Large Molecules (Macro Docking)

The radial shape functions used in *Hex* decay exponentially beyond about 35 Ångstroms from the chosen origin. This means that the shapes of proteins much larger than this are not represented well. One example of such a large protein is the viral-surface hemagglutinin molecule presented in the CASP II and CAPRI protein docking challenges. In order to dock such large molecules, *Hex* assigns multiple local coordinate systems to the larger molecule (assumed to be the *receptor*) and docks the ligand around each local coordinate frame on the receptor. Setting up the receptor coordinate systems is controlled by the **Controls ... Macro-Sampling** control panel.

The general approach is to construct a very low resolution spherical harmonic surface representation of the receptor (say, setting L=5 in the *Harmonics Control* panel), and then

to cover this surface with a large number of spheres. These spheres are placed using the surface normals of each triangular patch used to draw the harmonic surface. The spheres are then iteratively *culled*, where the sphere with the greatest overlap with its neighbours is culled at each iteration. This is repeated until some pre-set number of spheres (default 25) remain - these should still cover the surface, but be reasonably well-dispersed. The positions of these spheres are then used to generate initial docking orientations for the ligand over the receptor, and an appropriate local coordinate frame is derived from the geometry. For multi-domain receptors, each sphere can be assigned to a source chain, and spheres that do not belong to a given chain may optionally be excluded. This gives a simple (but imperfect) way to limit the docking search to one of several symmetry-related domains (as in the hemagglutinin case, for example).

In order to set up such a calculation for an antibody/antigen system (where the antibody's binding site is known), it is a good idea to orient the ligand (antibody) such that the binding site faces the receptor - i.e. the principal intermolecular axis passes near the antibody hypervariable loops. This can be achieved by manually *editing* the antibody into position. Then, the macro-sampling algorithm will place the ligand (antibody) at each of the generated starting orientations and in each orientation the antibody will be transformed to face the receptor. Using the main *Docking Control* panel, a search range of 45 degrees should be set for both the ligand and receptor so that the docking search will gyrate each molecule about the local intermolecular coordinate system yet still keep each molecule roughly facing the other as defined by the starting pose.

## 5.11 Additional Docking Parameters

There exist a few further parameters which control the docking calculation but which are not accessible from the GUI. These parameters must be set using keywords in a macro file. For example, the steric overlap penalty factor has a default value of 11. This can be adjusted by running the example macro **factor\_q.mac**:

```
#
# steric_q.mac - change steric penalty factor Q (default=11).
#
# (this parameter can't be changed from the GUI yet).
#
factor_q 11
```

Similarly, another example macro file is **factor\_g.mac**:

```
#
# factor_g.mac - change electrostatic scale factor (def=700 J/mol).
#
# (this parameter can't be changed from the GUI yet).
factor_g 700
```

## 5.12 Molecular Matching

*Hex* superposes or *matches* pairs of molecular structures using the same 3D density representation as for docking. Superposition is very much like docking, except now the

search is for maximum similarity rather than maximum complementarity. Superposition calculations can only be performed once you have opened a *receptor* and a *ligand* molecule. If you want to superpose a pair of molecules that originate from the same PDB file, you will have to manually edit the molecules into separate PDB-format files. Superposition calculations are controlled by the parameters in the *Matching Control* panel. To calculate a superposition using the default settings (which are usually reasonable), use:

Controls ... Matching ... Activate

*Hex* will take a few seconds to calculate the steric density functions for each molecule. It will then systematically search over the range of angular and intermolecular distance samples given in the *Matching Control* panel. However, unlike docking, *Hex* first translates the ligand's centre of mass to coincide with that of the receptor. If the molecules are similar, this essentially reduces the search space to a rotational search (to a first approximation). Hence, the default distance range and angular samples are set to much smaller values than are used in a typical docking correlation search. Similarly, good global overlaps can be found using much lower-order correlations than needed for docking. Therefore, it's usually sensible to leave all the superposition search parameters at their default values. Nonetheless, the defaults generally give a search which significantly over-samples the search space, and only one or two distinct superpositions are likely to remain after clustering.

By default, superpositions are calculated using only the van der Waals density representation of each molecule. However, this can be changed with the *Search Mode* selector to match shapes using both the interior (van der Waals) and exterior (surface skin) density functions. This doubles the computational cost, but it can be useful when matching a small molecular fragment onto a surface patch of a larger molecule, because the skin-matching component ensures surface matches are favoured over trivial inclusion matches of the fragment within the body of the larger molecule.

The shape matching algorithm re-uses much of the docking code, and the *Matching Control* panel works in almost exactly the same way as for docking (see Section 5.4 [Docking Examples], page 20). One noticeable difference, however, is that similarity scores are calculated using a Carbo-like overlap score. This is essentially a normalised overlap volume, scaled onto [-1000,0] for compatibility with the existing clustering, ranking, and summary output code used by the docking module. In other words, *Hex* always thinks "negative is good."

NB. Prior to version 4.0, *Hex* used un-normalised overlap volumes for similarity scoring. Using normalised scores makes it easier to compare (and perhaps cluster) multiple molecules.

Work on a more efficient 6D matching search algorithm is in progress.

## 6 Miscellaneous

### 6.1 Macros

In *Hex*, macros (or scripts) are command files which contain a sequence of instructions equivalent to the commands that you might issue from the graphical user interface. To create a macro file, go to the *Macros* menu and select *Learn*. All subsequent operations that you perform (including opening files, editing molecules, changing colours, etc.) will be recorded. When you have completed the sequence of commands that you want to record, select the *Save* command in the *Macros* menu. This will produce a small window, prompting you for a file name in which to save the command sequence. The convention is to use a file name of the form **filename.mac**, although you could adopt your own convention.

Here is an example. Lets open an antibody structure, colour it according to the residue identities of the framework and hypervariable loop regions, and position the molecule (using the mouse) in a pleasing orientation. The command sequence might be:

```
Macros ... Learn                                # start recording
File ... Open ... Receptor ... 3hfl.pdb         # existing file
Controls ... Molecule ... Colour File ... 3hfl.col # existing file
Controls ... Hetero ... Display
Solvent ... solvent display off
Lock                                             # lock home view
Macros ... Save ... test.mac                   # save commands
```

Printing the file **test.mac** should show a command sequence similar to:

```
open_receptor    3hfl.pdb
set_colour_file  3hfl.col
display_solvent  0
button_active    3
cursor_rotation  -0.0161 0.0233
button_active    0
button_active    2
cursor_rotation  0.0121 -0.0295
button_active    0
lock_home_view   1
```

You can now re-execute these commands using:

```
File ... Close ... All
Macros ... Run ... test.mac
```

If you make a mistake while recording a macro and want to cancel the current recording, select:

```
Macros ... Forget
```

Note that running a macro *does not* update the state of any toggles or any numerical values in the graphical user interface. Thus the state of the display and the values shown in the GUI controls may become inconsistent after running a macro. Nonetheless, macros are useful for running canned sequences of commands and for running batch jobs. Since a macro

file may invoke another macro, it is quite easy to set up a sequence of docking calculations, for example, using the same docking parameters on a number of trial complexes.

Here is a more complicated example using several macro files, starting with the top level macro, **dock\_ptc.mac**, which is provided in the **examples** directory:

```
#-----
#
# dock_ptc.mac
#
docking_receptor_samples  492
docking_ligand_samples    492
docking_alpha_samples     128

receptor_range_angle      180
ligand_range_angle        30
twist_range_angle         360

r12_range                  21
r12_step                   0.75
grid_size                  0.6

docking_main_scan          16
docking_main_search        25

run_macro ptc.mac

run_macro randomise_ligand.mac

activate_docking

#-----
#
# ptc.mac - loads unbound protein subunits in standard orientation
#

close_all

open_receptor  2ptn_e.pdb
open_ligand    4pti_i.pdb
open_complex   2ptc.pdb

fit_ligand

#-----
#
# randomise_ligand.mac
#
```



```

moving_thing 1      # (edit 0=receptor, 1=ligand, 2=complex)
randomise_molecule # (i.e. randomise the ligand orientation)
commit_view        # (commit changes)
moving_thing -1     # (done editing)
#-----

```

One could run this macro sequence interactively, and then use the **Page/Up** and **Page/Down** keys to step through displayed solutions. However, when testing the docking algorithm, or when performing multiple docking runs, its probably easier (and of more interest) to examine the calculated energies and ranks of each predicted docking orientation. Since these values are printed as the calculations proceed, its often convenient to run the whole thing in batch and to capture the results in a log file. For example, at the unix prompt, type:

```

hex <dock_ptc.mac >dock_ptc.log # Hex goes into the background
ps -ef | grep hex              # check background process running

```

The various docking parameters are described in more detail in Chapter 5 [Docking Molecules], page 18.

**TIP:** Very little checking is done when reading a macro file. Hence you should always use the GUI, via **Macros ... Learn** and **Macros ... Save**, to find legal values for the macro commands. Using values which are not available in the GUI may crash the program or produce meaningless results.

## 6.2 Hetero Atoms

When *Hex* loads a protein or DNA structure, it tries to draw all atoms including any water molecules or other *hetero* atoms (such as ions and other small molecules) that it finds in the PDB file. The *Hetero Control* panel allows a certain degree of control over how such atoms are treated. The *Hetero Control* panel is activated using:

```
Controls ... Hetero
```

This panel allows you to modify the treatment of solvent and hetero atoms:

```

Display Solvent (toggle)
Enable Solvent  (toggle)
Display Hetero  (toggle)
Enable Hetero   (toggle)

```

When *Enable Solvent* is selected, all water molecules are treated as part of the structure when calculating dot surfaces or spherical harmonic surfaces, for example. Toggling this option excludes solvent from the surface calculation. The *Display Solvent* toggle may be used to eliminate all waters from the graphics display (but remember, they still exist (if enabled), as far as any calculations are concerned). Enabled solvent atoms are displayed in light blue: disabled atoms are displayed in grey. The *Hetero* toggles have a similar function. Similarly, the *Enable ARG/LYS* toggle allows the status of any arginine and lysine side chain atoms to be changed. Disabling these side chains during a predictive docking run generally reduces the sensitivity of the docking correlation, but is often highly beneficial in

the following molecular mechanics refinement step: This part of the program is still under development.

The *Solvent Colour* button activates a simple colour chart which may be used to select an alternative colour with which to display enabled solvent atoms.

The *Cull Solvent* button calculates which water molecules are completely buried within a protein - and *disables* those that are not. The culling calculation uses the dot surface algorithm to determine the accessibility of each water molecule. The van der Waals surface of each atom in the structure is covered with dots: those dots which are occluded by neighbouring atoms are deleted in a recursive search, so that any atom with no surviving dots must be completely inaccessible to a probe sphere. Any water molecule that has surviving surface dots must, therefore, be accessible to the probe and is *culled*: i.e. removed from the surface atom list. The algorithm is repeated (automatically) until no more waters can be removed. Usually this takes from one to four cycles, depending on how many shells of solvent surround the molecule.

As an alternative to this automatic calculation, it is also possible to manually select water molecules (or any other atoms) to be culled. Select *ID* picking mode, and pick those atoms you wish to cull. Pressing the *Toggle Picked IDs* button (in *Hetero Control*) will toggle the status of any picked atoms.

Finally, using the *Apply to* selector, you can choose to apply these operations to all molecules (the default) or only to a selected molecule. If more sophisticated atom selections are required, it will probably be necessary to edit PDB files manually, before loading them into the program.

## 6.3 Hardcopy Output

*Hex* supports JPEG, PNG, and Postscript hardcopy output. Just compose your scene and then use the appropriate **File ... Print** option to write the scene to an image file. The **File ... Print** menu also contains a special *Pipe* option. This causes the molecular coordinates for the current scene to be piped (in the sense of a Unix pipe) to a script in the **\$HEX\_ROOT/pipes** directory, which can be used to load the current structures directly into an external program such as GRASP or Molscript. The **\$HEX\_ROOT/pipes** directory contains example scripts to run these programs.

## 6.4 Compressed Files

*Hex* 3.4 has full support for gzip (.gz) and bzip2 (.bz/.bz2) file compression formats. If you specify an output file name with one of these file name extensions, you will automatically get the corresponding type of compressed output. Similarly, if any input file has one of these extensions, *Hex* will automatically decompress the file as it reads it.

**TIP:** If you have installed a copy of the PDB (e.g. from the PDB CDROM disc set) on your hard drive, you can use *Hex* to view the structure files without first having to decompress them. Just point *Hex*'s file selection widget at the top level of your PDB directory and start visual browsing!

## 6.5 Environment Variables

*Hex* uses several environment variables to locate directories and data files. Most of these are optional, as described in the table below. The non-optional environment variables are defined automatically if you use the **hex\_configure.bin** script to install *Hex*.

Name	Status	Default	Description
HEX_CACHE	optional	\$HEX_ROOT/cache	locates a cache directory for the translation matrices: <b>highly recommended</b>
HEX_COLOURS	optional	\$HEX_ROOT/examples	locates a directory of <i>Hex</i> colour files
HEX_CPUS	optional	1	the default number of CPUs to use
HEX_DATA	optional	\$HEX_ROOT/data	locates non-standard <i>Hex</i> data files
HEX_LOG	optional	hex.log	defines the name of the current log file
HEX_MACROS	optional	\$HEX_ROOT/examples	locates a directory of <i>Hex</i> macro files
HEX_PDB	optional	\$HEX_ROOT/examples	locates a directory of PDB files
HEX_PIPE	optional	\$HEX_ROOT/pipes	locates a directory of <i>Hex</i> pipe scripts
HEX_ROOT	required	none	locates the main <i>Hex</i> installation directory (e.g. /usr/local/hex)
HEX_STARTUP	optional	none	locates a start-up macro script (e.g. \$HEX_ROOT/data/startup_v4.mac)
HEX_STEREO	optional	yes	defines whether a stereographic visual is requested by default
HEX_VERSION	optional	4	the default version of <i>Hex</i> to use

Additionally, you should ensure that your **PATH** contains the **\$HEX\_ROOT/bin** directory.

## 6.6 Command Line Options

The general command-line format to invoke *Hex* is

```
hex [-options] [pdbfile(s)]
```

where **options** may be a combination of:

```
-v#           (where # is a version number/string - e.g. 3d, 3c)
-ncpu n       (where n is the number of CPUs to use)
-nice n       (runs at lower priority: n a "nice" value)
-noexec       (don't put a batch run in the background)
-stereo       (request a stereographic window)
-s            (same as -stereo)
-nostereo     (request a non-stereographic window)
-nos          (same as -nostereo)
-stdout       (write messages to terminal, not separate window)
-kill         (kill all your Hex processes)
-log logfile  (or -l, write log of entire session to file)
-l logfile    (same as -log)
-pdb pdbfiles (load up to 3 PDB files to be displayed)
-browse       (same as -pdb, but forces interactive mode for browser)
-noligand     (treat two PDB files as receptor + complex)
```

```
-2          (short form of -noligand: superposes two molecules)
-pos        (position ligand near receptor - the default)
-nopos      (don't mess with ligand coordinates)
-e macfile(s) (execute up to 3 macro files)
```

### 6.6.1 Loading Three Structures Together

Load three PDB files which contain a *receptor*, a *ligand*, and an existing *complex* structure (to be used to calculate RMS deviations of the docking predictions), and execute a macro file of docking commands, writing the results to a named log file:

```
hex r.pdb l.pdb c.pdb -e docking_job.mac -l docking_job.log
```

### 6.6.2 Loading And Superposing Two Structures

Load a *receptor* and a *complex* (i.e. no *ligand*), and superpose the complex onto the receptor:

```
hex -2 r.pdb c.pdb
```

### 6.6.3 Docking With Macro File And Log File

Run a docking calculation (assumed to be fully specified in a macro file), using 2 CPUs:

```
hex -ncpu 2 -e job.mac -l job.log
```

### 6.6.4 Docking With File I/O Redirection

Run the previous example using I/O redirection:

```
hex -ncpu 2 <job.mac >job.log
```

### 6.6.5 Serialising Several Batch Jobs

If both *stdin* and *stdout* are not terminal devices, *Hex* automatically puts itself into the background. When running a Unix script with a series of different jobs, this behaviour should be suppressed using the `-noexec` option:

```
hex -ncpu 2 -noexec <job1.mac >job1.log # job2 starts after job1
hex -ncpu 2 -noexec <job2.mac >job2.log
```

### 6.6.6 Using *Hex* As a Web Browser

On Unix systems, *Hex* may be used as a web browser helper application for PDB files by specifying that *Hex* should be invoked when the browser receives a MIME type that corresponds to a PDB file (e.g. chemical/x-pdb). See the `hex_browser` file in the `$HEX_ROOT/bin` directory for details. If anyone implements something similar for MS-Windows, please let me know!

## 6.7 Examples Directory

The **examples** directory, under the main **hex** directory, contains PDB data files of examples of two protein complexes: HyHel-5/lysozyme and BPTI/Inhibitor. It also contains short *macro* files to load the subunits of these complexes. Unless you have changed the values of the HEX\_PDB and HEX\_MACROS environment variables, *Hex* will look in the **examples** directory by default. Select:

```
Macros ... Run
```

and then select one of [**3hfl.mac**, **2ptc.mac**], or [**hfl.mac**, **ptc.mac**]. This will open the files that contain the atom coordinates of either the crystallographically determined complex (first pair) or the coordinates of the separately determined protein subunits (second pair), superposed on the corresponding complex structure. In both cases the structure of the complex should appear as a thin grey skeleton.

The **examples** directory also contains sample colour files, **\*.col**, and a few other macro files, **\*.mac**, which you might wish to examine. In particular, the **startup.mac** file explains how to select an initial colour scheme, for example. It also shows how to switch off the initial logo display if you prefer to start with a blank screen, and how to change the type of browser (Netscape, by default) used to display this User Manual on-line.

Please note: The example docking scripts **dock\*.mac** will only work correctly if *Hex* can find the relevant PDB files and related macros. Once you've defined the HEX\_PDB and HEX\_MACRO environment variables, to point to your own directories, you should copy the appropriate files from the **examples** directory into these new directories if you still want to use these scripts.

A much more extensive set of docking test cases can be obtained from *Hex's Home Page* (<http://www.biochem.abdn.ac.uk/hex/>).

## 6.8 Bugs And Known Limitations

Please report any bugs/suggestions to the author (see Section 6.12 [Contacts], page 36). Described below are some known limitations, some of which might never be fixed.

### 6.8.1 No Multi-Processing on MS-Windows

On Unix, *Hex* can exploit multiple processors in most of its calculations. This has been implemented using the Unix “fork” feature, which doesn't exist in the MS-Windows operating system. So currently, the MS-Windows version can only use one CPU. I haven't bothered to write a Windows “threads” version of the docking module, because I assumed most MS-Windows users would likely only have a single-CPU anyway. But I could be persuaded otherwise if there is sufficient demand.

### 6.8.2 GUI and Graphics Freeze During Docking

Although it was claimed in the new features section that the GUI and graphics window remain responsive even during docking, there are some stages in the calculations where its

not possible to respond to user interaction. This is especially true during multi-processor docking runs because its too difficult to preempt the sub-tasks. [Technical note: If you're interested in this kind of thing, despite appearances, *Hex* is a purely single-threaded application (not counting “fork” and “exec” calls)].

### 6.8.3 Macros

When *Hex* runs a macro, it doesn't update the state of any toggles or any numerical values in the graphical user interface. Thus the state of the display and the values shown in the user interface controls may become inconsistent after running a macro.

### 6.8.4 Non-Standard Residues

Non-standard or substituted amino acid residues may not be drawn properly, because *Hex* requires an entry in the **atom.type.dat** and **atom.bonds.dat** files for each type of atom and bond, respectively. However, *Hex* makes a reasonable attempt to draw the bonds of unrecognised molecules (typically small ligands). The sequence **File ... Open ... Dataset** is intended to allow user-specific atom and bond data files to be loaded, but this isn't properly implemented yet.

### 6.8.5 Hardcopy Fonts

The *Graphics Font* selected from the font menu panel is not propagated to Postscript. All printed text always appears in Times-Roman.

### 6.8.6 Colouring Multiple Models

The molecule colouring options don't always work correctly for structures with multiple models.

## 6.9 The Test Functions

Surface sampling using an *icosahedral tessellation* and surface parametrisation using *spherical harmonic* functions are both central to the shape similarity and complementarity calculations in *Hex*. In *Test Mode*, you can view the spherical harmonic basis functions and the icosahedral tessellations used in the calculations. Go to the *File* menu and select:

**File ... Open ... Test**

You now should see a spherical grid plotted as a white mesh. Each grid cell has approximately the same area. Formerly, this grid was used as a look-up table to map an arbitrary spherical coordinate  $(\theta, \phi)$  onto the nearest vertex of an icosahedral tessellation, but its no longer used in the current version. You can change the number of grid cells using the *Mesh Order* slider in the *Harmonic Surface* control panel. Select:

**Graphics ... Harmonic Surface ... Mesh Order ... 10**

The *Mesh Order* slider controls the number of vertices to be used in an icosahedral tessellation, by specifying the number of subdivisions made along each edge of a regular icosahedron. (It also indirectly controls the number of cells in the corresponding spherical grid).

You can view the icosahedral tessellation by selecting the *L=0* spherical harmonic function:

Controls ... Harmonics ... Order ... 0

and by clicking the *Enable Harmonics* button. You may need to adjust the zoom factor (bottom left slider) to get a better view.

TIP: The *Harmonics* button (which looks like a balloon: its supposed to represent the  $L=2, M=0$  harmonic function) on the right-hand border of the main window also acts as a toggle equivalent to the *Enable Harmonics* button.

You can now display arbitrary spherical harmonic functions using the *Order (L)* and *Degree (M)* sliders. Each function is plotted by evaluating the function at the angular coordinates of each icosahedral tessellation vertex and by setting the radial distance for each angular sample to that of the function value. You can control the number of sample points with the *Mesh Order* slider (above) and you can control the display style of the functions using the *Display Mode* selector of the *Harmonic Surface* control panel. Try:

Graphics ... Harmonic Surface ... Display Mode ... Polyframe

Note that when you rotate or translate the scene using the mouse buttons, the display reverts to wire-frame rendering until you release the button. This is usually faster than re-rendering polygons during the motion. The *Solid Motion* button (right-hand border, last button) can be used to toggle this behaviour.

The three sliders in the *Harmonics Control* panel labelled *Alpha*, *Beta* and *Gamma* are used to test Euler angle rotations of the spherical harmonics. Changing these values will cause the rotated function  $R(\alpha, \beta, \gamma)(Y_{l,m}(\theta, \phi))$  to be calculated and displayed. Visually, this should be identical to drawing the unrotated figure and then manually rotating it with the mouse by  $R(\gamma)$  about the  $z$ -axis,  $R(\beta)$  about the  $y$ -axis, followed by  $R(\alpha)$  about the  $z$ -axis. This is an important visual test because ensuring that the spherical harmonic functions can be rotated computationally is fundamental to *Hex*'s shape superposition and docking calculations.

Finally, using spherical harmonics to parametrise the surface shape of a cube provides a further (possibly perverse) test of the method. You could try:

File ... Open ... Cube

and then experiment with different display styles and surface resolutions. Using  $L=16$  gives a remarkably good *spherical harmonic cube*. In addition to rotating the cube manually, it can be rotated by rotating the harmonic basis functions (above) or, equivalently, by rotating the shape expansion coefficients by setting the *Rotate Coefficients* toggle in *Harmonics Control*.

for the order  $L$  should be kept at their default values except during the

TIP: Generally, all parameters in the *Harmonics Control* panel except above tests.

## 6.10 Technical Information

In order to run *Hex*, your system should have at least 64Mb main memory but preferably more (128 Mb or greater), and about 4 MB of disc space for the program and data files. The speed of the docking calculations can be increased by allocating an optional *disc cache* directory of up to about 100 MB. For molecular docking and graphics applications, I'd recommend buying the highest-spec Linux machine you can afford, but be sure to select a graphics card that has Linux support. I personally own a Pentium III Xeon system with a Quadro4 XGL700 graphics card (currently running RedHat 9.0). Its great.

The latest Linux version was built on a RedHat Pentium III system (RedHat 9.0), with version 2.4.20-8 of the kernel, XFree86 4.3.0, and compiled with gcc 3.2.2. Versions are also available for RedHat 8.0 (kernel 2.4.18-14, XFree86, 4.2.0, gcc 3.2-7), RedHat 7.3 (kernel 2.4.18-3, XFree86 4.2, gcc 2.96), RedHat 7.2 (kernel 2.4.7-10, Mesa 3.5, XFree86 3.3.6), and RedHat 6.2. However, more recent versions of *Hex* may not be available for earlier operating system versions (I don't have a room full of machines with different O/S versions!). It is advisable to select a version which is *no newer* than your own system. However, if you have a good graphics card for which there is hardware support, you may wish to try using the *shared-link* executable. This does not have OpenGL bound into the executable, but instead expects to find the appropriate (possibly vendor-supplied) libraries at run-time. A *shared-link* executable will be *required* for PC/Linux hardware stereo support.

The Silicon Graphics version was built on a MIPS R5000 O2 system running IRIX 6.5, and compiled using `-n32 -mips4`. The SGI executable is known to run on R5000 and R10000 systems. The SGI executables should work on earlier versions of IRIX (down to 6.1, at least).

The Sun version was built on an UltraSparc E450 running SunOS 5.8, and using the OpenWindows version of OpenGL. It was compiled to make a *generic* SunOS executable which should run on other UltraSparc systems.

The Windows version was built on a Pentium III 686 system running Windows XP, and using the **MinGW** (<http://www.mingw.org/>) development environment. The binary should work on other Windows systems.

## 6.11 Caveats

Please remember that *Hex* is essentially a research program and it is provided "as is", without any guarantee of updates or user-support. I always try to respond to problems, and I welcome suggestions for future enhancements. However, if you do have a question, suggestion, or if you think you've found a bug, *please* check the FAQs first (see Appendix E [FAQs], page 49), and check *Hex's Home Page* (<http://www.biochem.abdn.ac.uk/hex/>) to make sure you're using the latest version.

## 6.12 Contacts

Author: **Dave Ritchie** (<http://www.csd.abdn.ac.uk/~dritchie/>). Before e-mailing me with a problem or question, **please first check the FAQs** (see Appendix E [FAQs], page 49).



## 6.13 Acknowledgements

Much of *Hex* was developed during projects (1996-2000) funded by the **BBSRC** (<http://www.bbsrc.ac.uk/>). *Hex* was written mostly in C, but also uses some C++ for the GUI. The new *Hex* GUI (version 4.0) was built with **FLTK** (<http://www.fltk.org/>). The *Hex* logo and icons were created with **The Gimp** (<http://www.gimp.org/>). The translation matrices used in *Hex* are calculated using the **GMP library** (<http://www.swox.com/gmp/>). Support for compressed files is thanks to the **zlib** (<http://www.gzip.org/zlib/>), **gzip** (<http://www.gzip.org/>), and **bzip2** (<http://sources.redhat.com/bzip2>) projects. The Linux version would have been impossible without the **Mesa** (<http://www.mesa3d.org/>) graphics library. Much of the **OpenGL** (<http://www.opengl.org/>) support from Mesa has been incorporated into **XFree86** (<http://www.xfree86.org/>) via the **DRI Project** (<http://dri.sourceforge.net/>). The MS-Windows version of *Hex* was built entirely under the **MinGW** (<http://www.mingw.org/>) environment (*Hex* has never been anywhere near a Microsoft compiler!). This manual was produced using **texinfo** (<http://www.gnu.org/software/texinfo/>). So its thanks to all these excellent Open Source projects for making *Hex* possible.

*Hex* uses the **Stride** (<ftp://ftp.ebi.ac.uk/pub/software/unix/stride>) program to assign protein secondary structures for cartoon displays. See Section A.2 [Stride Licence], page 41 if you have any doubts about whether you are entitled to use Stride.

I would also like to thank the following people for making significant programming contributions to *Hex*: **Ryan Cairns BSc** (FLTK port), **Ewan Lyle BSc** (ribbon cartoons), **Ioannis Zaferopoulos BSc** (solid models), **Russell Hamilton MSc** (macro docking displays), **Guillaume Valadon BSc** (surface colouring).

Over the last few years, developing *Hex* has become quite a personal hobby of mine. One day, *Hex* might even become famous. But obviously not yet, according to the *Hex Googlisms* ([http://www.googlism.com/what\\_is/h/hex/](http://www.googlism.com/what_is/h/hex/)). I quite like the one that says "*Hex* is not a persistent environmental contaminant." I hope *Hex* will eventually reach the more elevated status of: *Mostly Harmless* (<http://www.bbc.co.uk/cult/hitchhikers/guide/earth.shtml>)!

## 6.14 References

- *Evaluation of Protein Docking Predictions Using Hex 3.1 in CAPRI Rounds 1 and 2*, D.W. Ritchie (2003), *PROTEINS: Struct. Funct. Genet.* **52**, 98-106.  
[http://www.csd.abdn.ac.uk/~dritch/papers/ritchie\\_capri\\_paper.pdf](http://www.csd.abdn.ac.uk/~dritch/papers/ritchie_capri_paper.pdf)
- *Protein Docking Using Spherical Polar Fourier Correlations*, D.W. Ritchie and G.J.L. Kemp (2000), *PROTEINS: Struct. Funct. Genet.* **39**, 178-194.  
<http://www.csd.abdn.ac.uk/~dritch/papers/docking.pdf>
- *Fast Computation, Rotation, and Comparison of Low Resolution Spherical Harmonic Molecular Surfaces*, D.W. Ritchie and G.J.L. Kemp (1999), *J. Comp. Chem.* **20**, 383-395.  
<http://www.csd.abdn.ac.uk/~dritch/papers/matching.pdf>

- *Parametric Protein Shape Recognition*, D.W. Ritchie (1998), PhD Thesis, University of Aberdeen.  
[http://www.csd.abdn.ac.uk/~dritch/papers/dwr\\_thesis.pdf](http://www.csd.abdn.ac.uk/~dritch/papers/dwr_thesis.pdf)
- *Knowledge-Based Protein Secondary Structure Assignment*, D. Frishman and P. Argos (1995), *PROTEINS: Struct. Funct. Genet.* **23**, 566-579.  
<ftp://ftp.ebi.ac.uk/pub/software/unix/stride>

## 6.15 Citing *Hex*

When citing *Hex* in a publication, please cite whichever of the above articles seems most appropriate, and please also mention *Hex's Home Page*:

<http://www.biochem.abdn.ac.uk/hex/>.

# Appendix A Licences

## A.1 Hex Licence

This is a legal agreement between you, the LICENSEE, and the LICENSOR for use of the computer program *Hex*. It must be understood that by downloading or obtaining a copy of *Hex* by any other means, you agree to be bound by the following licence agreement.

BY INSTALLING, COPYING OR OTHERWISE USING *Hex* YOU AGREE TO BE BOUND BY THE TERMS OF THIS LICENCE AGREEMENT. IF YOU DO NOT AGREE TO THE TERMS OF THIS LICENCE AGREEMENT THE LICENSOR IS UNWILLING TO LICENCE THE SOFTWARE TO YOU. IN SUCH AN EVENT, YOU MAY NOT USE OR COPY THE SOFTWARE AND YOU SHOULD RETURN THE UNUSED PRODUCT WITHIN 7 DAYS.

### 1. Definitions

- (a) LICENCE means the terms and conditions contained herein.
- (b) LICENSOR means the University of Aberdeen, of Regent Walk, Aberdeen, Scotland, UK, as owner of the software comprising the computer program *Hex*.
- (c) SITE means a single computer or internal computer network operated by the LICENSEE at the premises of the LICENSEE specified when *Hex* was ordered or installed.

### 2. Grant of Licence

- (a) The LICENSOR grants the LICENSEE a non-transferable and non-exclusive licence to use *Hex* in connection with computers only on the SITE to which the LICENCE applies.
- (b) The LICENSEE will not, under any circumstances, reverse engineer, decompile or disassemble *Hex*.

### 3. Licence Fee

- (a) In consideration of the LICENCE granted pursuant to Section 2, the LICENSEE shall pay to the LICENSOR the applicable LICENCE FEE within 30 days of receipt of an appropriate invoice prepared by the LICENSOR.
- (b) For Academic and Governmental SITES, the LICENCE FEE is waived.

### 4. Transfer of Licence

- (a) The LICENSEE shall not in any way sublicense, rent, assign or transfer this LICENCE or the computer program *Hex*.

### 5. Copyright

- (a) The LICENSOR owns the copyright and all and any other intellectual and industrial property rights in *Hex* and its associated documentation. You must therefore treat *Hex* and its associated documentation like any other copyrighted material (e.g. a book).
- (b) *Hex* and the associated documentation is protected by United Kingdom copyright laws, international treaty provisions, and all other applicable national laws.
- (c) The LICENSEE acknowledges that it does not and shall not acquire any title, copyright or any other intellectual property rights in *Hex* or the associated documentation.

### 6. Limited Warranty and Disclaimer of Warranty

- (a) The LICENSEE acknowledges that software in general is not error-free and that the existence of such errors shall not constitute a breach of this LICENCE.

(b) Save as expressly provided under this LICENCE, no warranty or conditions express or implied, statutory or otherwise as to condition, quality, performance, merchantability or fitness for purpose is given or assumed by the LICENSOR in respect of *Hex* and its associated documentation and all such warranties and conditions are hereby excluded save to the extent that this exclusion is prohibited by law.

#### 7. Limitations of Liability

(a) Except to the extent that such liability may not lawfully be excluded, the LICENSOR shall not be liable for damages arising out of or in conjunction with the LICENCE of *Hex* or its use or performance.

(b) In no event shall the LICENSOR be liable for any loss of profits, business interruption, loss of business information or other special consequential damages, even if the LICENSOR has been advised of the possibility of such damages, or for any claim against the LICENSEE by any other party.

#### 8. Termination

(a) This LICENCE agreement is effective from the date of purchase or installation, whichever is earlier, of the computer program *Hex*.

(b) The LICENSEE can terminate the LICENCE at any time by notifying the LICENSOR of its intention in writing.

(c) The LICENSOR can terminate the LICENCE, after providing the LICENSEE with 14 days prior notice and an opportunity to remedy the situation, if the LICENSEE fails to pay any amount due to the LICENSOR.

(d) The LICENCE shall terminate 30 days after written notice by either party in the event of any material or persistent breach by the other party of any of the terms of this LICENCE which is either incapable of remedy or remains unremedied at the end of the said period of 30 days.

(e) Upon termination of this LICENCE, the LICENSEE shall (i) discontinue use of *Hex* (ii) deliver to the LICENSOR all the software furnished by the LICENSEE pursuant hereto together with all copies thereof and (iii) erase or destroy any of *Hex* contained in the computer memory or data storage systems under the control of the LICENSEE.

#### 9. Entire Agreement

(a) This agreement constitutes the complete and exclusive statement of the agreement between the LICENSEE and the LICENSOR and supercedes all other oral or written proposals, prior agreements and other prior communications between the parties, concerning the subject matter of this agreement.

#### 10. General

(a) This agreement shall be governed by and construed in accordance with the laws of Scotland, and the parties prorogate the exclusive jurisdiction of the Scottish Courts.

(b) No representation or promise relating to, and no amendment of, this agreement shall be binding unless it is in writing and signed by both parties.

(c) The terms and conditions of this agreement shall prevail notwithstanding any variance with the terms and conditions of any order submitted by the LICENSEE.

(d) Except for the LICENSEE's obligation to pay the LICENSOR, neither party shall be liable for any failure to perform due to cause beyond reasonable control.

(e) No waiver by a party of any breach of any provision of this agreement shall constitute a waiver of any other breach of that or any other provision of this agreement.

(f) In the event that any of the provisions of this LICENCE are held to be invalid or unenforceable, this agreement shall be construed without such provisions.

## A.2 Stride Licence

The following text is reproduced from the Stride Documentation:

*“All rights reserved, whether the whole or part of the program is concerned. Permission to use, copy and modify this software and its documentation is granted for academic use provided that:*

- (i) this copyright notice appears in all copies of the software and related documentation;*
- (ii) the reference given below (Frishman and Argos, 1995) must be cited in any publication of scientific results based in part or completely on the use of this program;*
- (iii) bugs will be reported to the authors.*

*The use of the software in commercial activities is not allowed without a prior written commercial license agreement.”*

## Appendix B Installation Guide

When downloading *Hex* from the Internet, files should be copied in *binary* mode and saved as *source*.

### B.1 Microsoft Windows Installation

Just download and run the self-installer program **hex-4a-win.exe**. This adds a *Hex* icon to the Programs menu and adds the environment variable HEX\_ROOT to the registry. That's all you should need to get started! However, there are several other environment variables which you can set to customise *Hex*'s behaviour. These have the same names as the Unix/Linux version described below. In particular you may wish to define the HEX\_STEREO and HEX\_CACHE variables.

By default, *Hex* will use a stereographics window if a suitable graphics card is detected. However, this gives a slower drawing rate than non-stereo mode, even when viewing a non-stereo (zero parallax) scene. Setting HEX\_STEREO=no causes a non-stereographic window to be selected at start-up time, and hence should give faster graphics performance. During a docking calculation, *Hex* will write translation matrix files to the **\$HEX\_ROOT\cache** directory. However, you can define HEX\_CACHE to point to another directory (possibly on another disc with more space) to over-ride the default.

In Windows XP, environment variables are defined using the **Advanced** option in the *System* control panel.

### B.2 Unix/Linux Installation

You will need to download the installation script **hex\_configure.bin**, the generic run-time data file **hex-4a-rt.tgz** and one or more of the executables **hex-4a-sgi.tgz**, **hex-4a-sun.tgz**, or **hex-4a-lnx-\*.tgz** (but only take **one Linux executable!**). It is safe to install a new version into the same directory structure as an earlier version, unless you have changed any of the former scripts or data files. The distribution files should be installed using the shell script **hex\_configure.bin** by typing:

```
sh hex_configure.bin
```

This script is intended to simplify the installation process, and can normally be trusted to install *Hex* correctly, even if you have already installed an earlier version of the program. The script will add any necessary environment variables to your default shell environment. In cases where a central file server is used to serve files to different types of workstations, several different executables may be installed into a single **hex** installation directory.

If you prefer to install the program manually, you should create a **hex** directory, **cd** to that directory, and then uncompress the distribution files into it. For example, assuming you are installing the SGI version, use:

```
zcat hex-4a-rt.tgz | tar xvpf -
zcat hex-4a-sgi.tgz | tar xvpf -
```

If your **zcat** doesn't recognize gzip-ed files, use instead:

```
gunzip hex-4a-rt.tgz ; tar xvpf hex-4a-rt.tar
gunzip hex-4a-sgi.tgz ; tar xvpf hex-4a-sgi.tar
```

The tar `p` option is used to extract files with their original permission settings (i.e. world read and execute, as appropriate).

In order to make *Hex* work properly, your login script (`.login` or `.profile`, or whatever) should set the environment variable `HEX_ROOT` to the **hex** installation directory. You should also add *Hex*'s **bin** directory to your `PATH` so that (a) you can run *Hex*, and (b) *Hex* can find the files it needs under `HEX_ROOT`. These two steps are normally performed by the **hex\_configure.bin** script. Optionally, you can also specify directories that specify where *Hex* should start looking for colour files, macro files, and PDB files, and you can specify the location of a temporary cache directory (all except the **hex** installation directories are optional and must be created manually). You can also specify the default number of CPUs to use on a multi-processor system. These parameters are described in Section 6.5 [Environment Variables], page 31.

Here's a C-shell example (I have these lines in my `.cshrc` file):

```
setenv HEX_ROOT      /home/dritchie/hex
setenv HEX_PDB       /home/dritchie/pdb
setenv HEX_MACROS    /home/dritchie/hex_macros
setenv HEX_COLOUR    /home/dritchie/hex_colours
setenv HEX_DATA      /home/dritchie/hex/data
setenv HEX_CACHE     /tmp/dritchie/hex_cache
setenv HEX_STARTUP   /home/dritchie/hex/examples/my_startup_v4.mac
setenv HEX_CPUS      2
setenv HEX_STEREO    yes

setenv PATH $PATH:$HEX_ROOT/bin
```

For Bourne and Korn-shell users, the corresponding commands (in the `.profile` file) would be:

```
set HEX_ROOT =      /home/dritchie/hex
set HEX_PDB =      /home/dritchie/pdb
set HEX_MACROS =    /home/dritchie/hex_macros
set HEX_COLOUR =    /home/dritchie/hex_colours
set HEX_DATA =      /home/dritchie/hex/data
set HEX_CACHE =     /tmp/dritchie/hex_cache
set HEX_STARTUP =   /home/dritchie/hex/examples/my_startup_v4.mac
set HEX_CPUS =      2
set HEX_STEREO =    yes

set PATH = $PATH:$HEX_ROOT/bin
export PATH HEX_CACHE HEX_STARTUP HEX_CPUS HEX_STEREO
export HEX_ROOT HEX_PDB HEX_MACROS HEX_COLOUR HEX_DATA
```

In addition to the `README` and `LICENCE` files, the **hex** directory should contain the following 7 directories:

```
bin    exe    doc    data    examples    pipes    cache
```

Typing **hex** at the Unix command prompt should locate the script **hex** in the **bin** directory which then launches the appropriate executable from the **exe** directory. The **exe** directory may contains several executables (typically **hexZZ.mips4** and **hexZZ.sparc**, where **ZZ** is a version number). The **examples** directory contains several PDB files and example *Hex* macro files. Unless you set the above environment variables, *Hex* will first look in the **examples** directory for any macro and PDB files you want to use. The **data** directory contains the runtime data files necessary to colour and charge protein and DNA molecules, for example. The **pipes** directory contains Unix scripts which allow the molecular structures in the current *Hex* scene to be written directly to external programs such as GRASP or Molscript. The **cache** directory is the default location in which *Hex* will store its translation matrix files for docking runs. You may wish to use a different location for the cache by defining the **HEX\_CACHE** environment variable to point to an alternative directory.



## Appendix C Feature History

*Hex* is nearly seven years old (but it will always have a mental age of about two and a half)! For a long time, *Hex* lived quietly on my hard drive. Its first public release was when it was just two and a bit. This section lists how *Hex* has developed over the years.

### C.1 New Features In Version 4.1

*Hex* 4.1 is a bug-fix release.

- Double-clicking a directory in the file browser no longer crashes the program.
- Cartoons are now drawn correctly for chains with blank labels.
- Fixed start-up crash up on some SGI systems (JPEG lib version fault).

### C.2 New Features In Version 4.0

- Microsoft-Windows version now available, thanks to...
- New Graphical User Interface (GUI) - made with **FLTK** (<http://www.fltk.org/>).
- New Message Window for text output and session logging.
- New Progress Panel for docking calculations.
- New Cartoon display mode (see Section 3.3 [Cartoons], page 9).
- Shape matching now uses a Carbo-like similarity index (see Section 5.12 [Molecular Matching], page 25).
- GUI controls now available in full-screen mode (see Section 3.10 [Full Screen Mode], page 14).
- GUI controls and graphics window now stay responsive during docking(!).
- SGI mips3 version dropped - the O2 (mips4) is now the minimum SGI platform for *Hex*.

### C.3 New Features In Version 3.4

- Improved stereo support - works with nVidia's 3123 and later drivers (see Section 3.11 [Stereo Displays], page 14).
- New compressed file support - can read/write gzip (.gz) and bzip (.bz/bz2) files (see Section 6.4 [Compressed Files], page 30).
- New 3D density superposition algorithm - (see Section 5.12 [Molecular Matching], page 25).
- New User Manual - made with *texinfo* (<http://www.gnu.org/software/texinfo/>).

### C.4 New Features In Version 3.3

*Hex* 3.3 is a bug-fix release. Running *Hex* in batch mode (or when standard input was not a terminal device) was broken. The program would quickly crash with a SIGSEG error. Fixed now.

## C.5 New Features In Version 3.2

*Hex* 3.2 contains mostly minor bugfixes. However, stereo graphics is now available on Linux systems that have suitable hardware support:

- New stereo display option - type **hex -stereo** to request stereo (see Section 3.11 [Stereo Displays], page 14).

## C.6 New Features In Version 3.1

*Hex* 3.1 represents a fairly major upgrade relative to *Hex* 3.0, as follows:

- New *Full Screen Display* option - type **F** to toggle (see Section 3.10 [Full Screen Mode], page 14).
- New *Animation Mode* to cycle over docked orientations or multi-model structures (see Section 3.9 [Animation], page 13).
- New *Save Docking* option to write docking transformations to a disc file (see [Save Docking], page 24).
- New *Solid Surface* display modes to draw electrostatic and steric density functions (see Section 3.4 [Solid Surfaces], page 9).
- New *Radial Filtering* modes for docking scans: up to 25% speed-up (see Section 5.3 [Radial Filters], page 20).
- New *Radial Cutoff* option for viewing large molecules (see [Radial Cutoff Distance], page 7).
- New command **hex -kill** to clean up stuck processes (see Section 6.6 [Command Line Options], page 31).
- New *dynamically linked Linux executables* for hardware graphics support (see Section 6.10 [Technical Information], page 36).
- Improved multi-tasking - up to 20% speed-up on dual processor systems.
- Improved accuracy for translation matrices - some performance penalty when creating disc cache.
- Correlation limit increased to N=32 (for large memory machines) - not generally recommended.
- Improved surface contouring - slightly slower calculation, but smoother surfaces and faster graphics.
- Linux RedHat 7.2 version compiled with Intel icc compiler - up to 10% speed-up.
- Linux RedHat 7.3 version available (also compiled with icc).
- Removed limit of 65,535 atoms per molecule.
- Fixed obscure bug with model numbers in multi-model dockings.
- Fixed bug where mis-named gamma hydrogens were silently charged as mercury (Hg).

Note, there is still technically a PDB limit of 99,999 atoms per structure (Fortran I5 format), but *Hex* will try to read files that break this restriction. As of version 3.1, the models in multi-model structures are now numbered from 1, or use the actual model number given in the PDB MODEL record.

## C.7 New Features In Version 3.0

*Hex* 3.0 contains several new features and a number of improvements compared to *Hex* 2.4. These are mostly concerned with the docking algorithm and the graphics displays, although several bugs reported by users have also been fixed. The main new features are:

- Docking multiple "models" (e.g. from NMR structures)
- Docking very large molecules (as in the CASP2/CAPRI docking challenges)
- Clustering docking solutions
- Bumps filter for docking
- Molecular mechanics refinement of docking orientations (still under development)
- Docking twist search now accelerated by FFT
- Multi-file output of docking results
- New molecular surface calculation
- Solid Models: VDW spheres, licorice, tubes, etc.
- Lighting, with movable light
- Screen-shot output to JPEG, PNG, and Postscript files
- Special "pipe" option (e.g. to pass a scene to Molscript or Grasp)
- Better Linux support
- Improved command-line options
- Automated installation script: **hex\_configure.bin**

Existing *Hex* 2.4 users: Please note that *some of the parameter names used in macro files have changed from version 2.4*. Therefore, *some of your existing macro files may no longer work as expected*. This was unavoidable, given the many changes in the new version. Apologies for any inconvenience.

## Appendix D nVidia Stereo Configuration

Configuring an nVidia graphics card for stereo should be straight-forward. Just download the latest driver from <http://www.nvidia.com/view.asp?PAGE=linux>, and follow the instructions. However, as mentioned above, **make sure to de-install any earlier nVidia drivers first.**

Anyway, here's what the Device Section of my `/etc/X11/XF86Config` file looks like after editing nVidia's supplied template:

```
#
# Used 'lspci' command to verify PCI bus ID.
# Used NVidia README file for additional options.
#
Section "Device"
    Identifier          "NV AGP"
    VendorName          "nvidia"
    Driver              "nvidia"
    BusID               "PCI:1:0:0"
    Option "Stereo"      "1" # 0=off 1=DCC 2=blueline 3=onboard DIN
    Option "NoLogo"      "true"
    Option "UBB"         "true"
    Option "PageFlip"    "true"
    Option "WindowFlip"  "true"
    Option "Overlay"     "false"
    Option "UseEdidFreqs" "true"
    Option "NvAgp"       "1" # 0=off 1=nvidia, 2=AGPGART, 3=try 2, 1
EndSection
```

I verified these settings (and that stereo was enabled) by running the **glxinfo** program. Although my XGL700 has an on-board stereo DIN (3-pin) socket, I couldn't get a signal off this with the 3123/4191 drivers. Currently, stereo synching only seems to work in DCC (Data Control Channel) mode. This requires a monitor cable "splitter", to which the stereo glasses are connected. Such "splitters" often come included with stereo glasses kits. However, nVidia's 4349 driver claims to support DIN stereo output, but I haven't tested this yet. For best performance, use nVidia's AGP driver (part of NVidia's driver distribution), and NOT the Linux AGP driver (`/dev/agpgart`, etc.). Also, use a kernel built with the MTRR option (memory type-range registers) if your machine supports this.

## Appendix E Frequently Asked Questions

Actually, the questions listed below aren't so frequently-asked at all. As of April 2003, the program has been downloaded by about 1,500 people (about 600 downloads were obviously from academic or commercial sites), resulting in about a dozen problems/queries. Here they are.

- *I noticed you supply only binaries. Is there any chance of getting a copy of the source code?*

In general, the answer is no. At least not yet. Hex represents over seven years of work and it implements some ideas that have not yet been published: Gee, research is pretty competitive these days! I'd also like to keep open the possibility of potential future commercialisation, which might be difficult if the source is freely available. If your main interest in the source is just to poke around to see how it works, there are other OpenGL-based molecular graphics packages which do provide source that you could take a look at instead (e.g. VMD (<http://www.ks.uiuc.edu/Research/vmd/>), MolMol (<http://www.mol.biol.ethz.ch/wuthrich/software/molmol/>)). If you're more interested in the computational parts (spherical harmonics, Laguerre polynomials, etc.), these should be quite easy for any reasonably competent C or Fortran programmer to code up anyway. In terms of lines of code, this represents only a very small proportion of the program. On the other hand, if you have any novel or interesting research projects you might want to collaborate on, then I could probably be persuaded to cut a deal! In any case, if you have a genuine interest in some parts of the code, please contact me personally.

- *I downloaded the Linux version of Hex, followed all the instructions, but still nothing works. What do I try next?*

Hmm. Well, Hex is known to run on Redhat 6.0, 6.1, 6.2, 7.0, 7.1, 7.2 and 7.3 releases of Linux. But RedHat 7.1 was a bit "dodgy" and I wouldn't recommend that. I'm not aware of any (recent) Linux systems it doesn't run on. However, I can't guarantee that Hex will run on every Linux system, because a lot depends on where the run-time libraries are located (eg. /usr/lib/libc.so, etc.), although I've tried to minimise such dependencies.

If nothing happens when you type `hex`, it's probably a problem with the `HEX_ROOT` and `PATH` variables (check the README file). If these look OK, change directory to the `hex/exe` directory and type `./hex2d.i586` to start the program without the aid of the front-end startup script - it should give you a graphics window with the Hex logo on a black background. The 2d part of the filename corresponds to version 2.4 - if you have a different version of the program, the executables will have slightly different names. Anyway, if that works, the problem is definitely with `HEX_ROOT` or `PATH` - in which case, check that `HEX_ROOT` is set to the directory you installed hex in (i.e. `/your/stuff/hex` without anything after the hex bit): also check that the `PATH` variable includes `$HEX_ROOT/bin` - i.e. `/your/stuff/hex/bin` in amongst the other colon-separated bits of the `PATH` (sorry if this is all obvious to you, but different people have different levels of Unix knowledge). You should be able to type `which hex` and get back `/your/stuff/hex/bin` if the `PATH` is properly set up.

If running stand-alone `./hex2d.i586` doesn't work, the next thing to try is the `ldd` utility. This shows the dependency list of any shared libraries that a program was linked against:

```
% ldd hex2d.i586
```

The output on my Linux system looks like this:

```
libX11.so.6 => /usr/X11/lib/libX11.so.6 (0x40014000)
libXext.so.6 => /usr/X11/lib/libXext.so.6 (0x400bd000)
libXp.so.6 => /usr/X11/lib/libXp.so.6 (0x400c9000)
libSM.so.6 => /usr/X11/lib/libSM.so.6 (0x400d3000)
libICE.so.6 => /usr/X11/lib/libICE.so.6 (0x400dd000)
libm.so.6 => /lib/libm.so.6 (0x400fb000)
libc.so.6 => /lib/libc.so.6 (0x40117000)
/lib/ld-linux.so.2 => /lib/ld-linux.so.2 (0x40000000)
```

There are no references to Mesa or Motif, because these were linked statically into the executable. On my system, /usr/X11 is a link to /usr/X11R6. Here's what I have in the /etc/ld.so.conf file (which I think is a minimal default with Linux):

```
/usr/lib
/usr/X11R6/lib
```

If there are any blanks in the ldd output or if the version numbers of the libraries in your /lib directory are hopelessly below the numbers here, then this could be the problem: update your libraries or make links from the required library names to the libraries you currently do have (?).

Otherwise, you're out of luck for the moment - but I'd appreciate it if you could send me some details of your system (e.g. Linux vendor & release, output from `uname -a`, etc.) and particularly the exact message you get after typing `./hex2d.i586` - I'll try to figure out what needs to be done and if possible make up a new Linux release to fix it.

- *I downloaded the Sun version of Hex, followed all the instructions, but still nothing works. What do I try next?*

Sun machines are probably the systems I know least about: they don't seem to give quite the same transparency across different hardware and CPU configurations as does IRIX, for example (or is this just my ignorance?). Anyway, similar comments to Linux apply, as above. Here's what Hex was built on:

```
% uname -a
```

```
SunOS hostname 5.7 Generic_106541-12 sun4u sparc SUNW,Ultra-4
```

And here's what the ldd output looks like.

```
% ldd hex3.sparc
```

```
libGLw.so.2 => /usr/lib/libGLw.so.2
libGLU.so.1 => /usr/lib/libGLU.so.1
libGL.so.1 => /usr/lib/libGL.so.1
libXm.so.4 => /usr/lib/libXm.so.4
libXt.so.4 => /usr/lib/libXt.so.4
libX11.so.4 => /usr/lib/libX11.so.4
libXext.so.0 => /usr/lib/libXext.so.0
libc.so.1 => /usr/lib/libc.so.1
```

```

libm.so.1 =>      /usr/lib/libm.so.1
libintl.so.1 =>   /usr/lib/libintl.so.1
libXmu.so.4 =>    /usr/openwin/lib/libXmu.so.4
libdga.so.1 =>    /usr/openwin/lib/libdga.so.1
libSM.so.6 =>     /usr/openwin/lib/libSM.so.6
libICE.so.6 =>    /usr/openwin/lib/libICE.so.6
libsocket.so.1 =>      /usr/lib/libsocket.so.1
libnsl.so.1 =>      /usr/lib/libnsl.so.1
libdl.so.1 =>      /usr/lib/libdl.so.1
libmp.so.2 =>      /usr/lib/libmp.so.2
/usr/platform/SUNW,Ultra-4/lib/libc_psr.so.1

```

OpenGL for SunOS is available at: <http://www.sun.com/software/graphics/OpenGL/>.

- *I downloaded the SGI IRIX version of Hex, followed all the instructions, but still nothing works. What do I try next?*

Hex should work “out-of-the-box” for IRIX 6.1 or higher. Apart from making a mistake with the HEX\_ROOT and PATH variables, the only other reason things might not work is if you have a \*very\* reduced IRIX installation without all the necessary run-time libraries, or if your system is set up with an unusual locale.

Please complain to your system administrator. If s/he manages to fix the problem, please let me know the story: it might save other people some grief in the future.

- *Why does Hex print a message about a Mesa configuration file?*

Actually, its the Mesa code that prints the message. This can happen when Mesa is already installed on your system, but the installed version (as cited in the /etc/mesa.conf file) differs from the version that Hex was built with. The Hex program is normally statically linked against Mesa, so its not necessary to explicitly install Mesa to run Hex. Just ignore the message. Or add a null function entry that matches the Mesa version in the message into /etc/mesa.conf to suppress it.

- *I noticed you only provide an i586 executable for Linux. I have an i686/i786 system, so could you supply a binary for my machine. It might run faster?*

I compared the docking performance of *Hex* compiled for a 686 processor on my 686 system with a 585-compiled version, and there was hardly any difference. Docking performance depends almost entirely on the efficiency of a few floating point operations, and the larger 686 instruction set doesn’t make floating point operations go any faster. Having said that, compiling with Intel’s *icc* (<http://www.intel.com/software/products/compilers/>) gives about a 10% speed-up over GNU’s *gcc-2.96* (<http://gcc.gnu.org/>), and the release versions of *Hex* are compiled with *icc* whenever possible (sorry, GNU).

- *I want to display and dock a protein with non-standard residues. What do I do?*

The \$HEX\_ROOT/data directory contains several files (**residue\_types.dat**, **atom\_bonds.dat** **atom\_names.dat**, **atom\_types.dat**) which define the atom connectivity, charges, and names of non-standard residues. You will need to define new entries in these files to define your new residues. Probably the easiest approach is to identify the most similar existing amino acid and to copy/rename/edit the entries. You may need to calculate/guess some partial charges for the new atoms.

- *How can I refine the results from a docking correlation?*

It is possible to further refine results from the docking correlation in *Hex* version 3. This “refinement” applies a soft molecular-mechanics energy evaluation and/or minimisation to the top 1000 orientations. However, if the amount of conformational change on binding is large, this refinement could eliminate what was a good solution. On the other hand, if the conformational change is small, then the calculation should lower the energy of a good orientation and significantly raise the energy of other orientations. I think its hard to assess how good the predicted orientations might be, and which of them might correspond to the actual solution. It is certainly hard to devise a scoring function which can reliably eliminate “false-positives” (Camacho & Vajda, Curr Op Struct Biol, 2002 12:36-40). Camacho & Vajda, and others, have proposed using a combination of algorithms, and to look for consensus orientations, but I have doubts. Personally, I think the surest approach is to use whatever experimental or bioinformatics evidence (e.g. correlated mutations) might be available to help suggest the location of the binding sites, and then to use a docking algorithm to create some feasible models which can subsequently be challenged by lab-based experiments.

- *How can I perform a purely electrostatic correlation?*

Its not possible to do a pure electrostatic correlation in *Hex*. However, it should be possible to increase the weight of the electrostatic correlation in a shape + electrostatic calculation. For example, if you create a small *macro file* containing

```
factor_g 7000
```

and then run this macro using the **Macros . . . Run** menu, all subsequent docking calculations will have electrostatic energies scaled up by a factor of 10. Thus electrostatics should dominate. Generally, I would say that shape complementarity is more important that electrostatics, but if you know electrostatics are important for a given system, then this may be worth trying.

- *When I enable electrostatics, I only get one docking solution. What is going on?*

Its likely that your structures contain unrecognised residues, and/or unrecognised atoms. *Hex* assigns a default charge and radius to any unrecognised atoms, normally based on the first letter of each atom name. These defaults are usually reasonable, but if a structure has a large number of unrecognised hydrogens, *Hex* might assign 0.5e to each hydrogen to give a highly positively charge protein. A pair of such proteins will have a very unfavourable electrostatic interaction, and docking such a pair will give a total of zero low energy orientations. In order to avoid having zero-length arrays within the program, *Hex* forces at least one solution to be reported.

- *What is the licensing fee for commercial user?*

There is currently no licence fee for commercial users. But this does not mean the software is “free”. When you download or otherwise obtain a copy of *Hex* you are agreeing to be bound by the *Hex* Licence Agreement. You are also asked to obtain prior agreement with the author if the program is to be used for profit. This might seem to be unnecessarily complicated, but the intention is to make the software available and to publicise the algorithms used, without compromising the possibility of potential future commercialisation. These days, universities like to protect their assets, and I want to protect my assetc ;-).



- *Whenever I run Hex, I get a whole bunch of messages saying “\*Warning\* OpenGL says - invalid enumerant”. What does this mean?*

This only seems to happen on SGI machines. There is internal diagnostic code within *Hex* to check on the status of the OpenGL engine after each screen refresh. I can't see anything that's actually *wrong* in the generated graphics, and there don't seem to be any adverse effects on hardware that show this message. Just ignore it!

- *What is the reference energy for electrostatic calculations in Hex, and in thermodynamic terms are you working with G or U?*

In *Hex*, the reference (zero) energy point is for two proteins at infinite separation. i.e. zero interaction. Negative scores are favourable, positive unfavourable (i.e. the molecules interpenetrate, or have poor surface contacts). The electrostatic energy *Hex* calculates corresponds to the classical internal energy (U) of a system of point charges. The shape complementarity score, or “hydrophobic energy”, is scaled to comparable units (but forced to have more negative energies). This pseudo energy is also closer to U than G, but could easily be in error by 100's of KJ/mol compared to experimental measurements. I have compared calculated *Hex* energies of complexes with equilibrium constants (i.e. ignoring the difference between U and G due to entropy) for some antibody/antigen complexes and found no correlation. So, the calculated energies are pretty meaningless on an absolute scale. But I'm sure this is also true of most (all?) other macromolecular docking software.

- *When I change some of the parameters in the docking control panel, such as the inter-molecular distance, I get different docking results. What's going on?*

The first few controls in the Docking Control panel define the search increments that *Hex* will use during a docking search. If you increase the number of steps (i.e. use more and smaller steps) then the rank of the “right” orientation is likely to be reduced because *Hex* will find more low-energy false-positive orientations during its search. This effect can largely be alleviated by ensuring you *cluster* the generated solutions using the Clustering Control panel. In general, it's better to over-sample the search space and then cluster the solutions rather than risk missing good solutions by under-sampling in order to make the program run faster.

The default value of the Distance Range in the Docking Control panel may be too small for large protein-protein complexes. Hence, if you find that increasing the distance range gives a completely different set of docking orientations, it's likely that you were seriously under-sampling the search space in the earlier run. In other words, if the distance range is too small, the program is not going to explore all possible surface-surface contacts as one molecule is rotated against the other.

*Hex* samples radial distances “symmetrically” from the starting orientation according to (Starting Distance) +/- (Distance Range)/2 in equal steps of +/- (Step Size). One way to work out what distance range to specify for a global search is to sketch each protein as a plane cross-section in such a way that the plane chosen for each protein includes its centroid, and the largest and smallest radial rays from the centroid to the surface. Then, set the initial inter-centroid distance (the starting distance) to the average of the sums of the smallest and largest radii. For example, if the smallest radii sum to 28Å, and the largest radii sum to 46Å, you should set the starting separation to  $(28+46)/2=37\text{Å}$ , and the Distance Range to  $2*(46-37)=18\text{Å}$ . Using the default Step Size (0.75Å), *Hex* will then

explore  $18/0.75=25$  trial distances (i.e. 12 inward and 12 outward distance steps, plus 1 for the initial distance).

In practice, it's often not possible to calculate the radii exactly, and hence set an optimal initial intermolecular separation. An alternative approach is to enable the Radial Envelope Filter, and to set a large Distance Range. When the radial filter is enabled, *Hex* will use low-resolution spherical harmonic surface approximations of each surface to select which intermolecular distances to evaluate at each angular pose of each molecule. However, because these surface representations are inexact (they assume the proteins are globular, or star-like), there is a possibility that some orientations that should be evaluated might be skipped.

- *I loaded a receptor and a ligand into Hex, ran a default docking calculation, but nothing seemed to happen. At the end of the run, the ligand hadn't moved! What's going on?*

*Hex* should always place the ligand near the receptor in tightly-fitting orientations. You should get a ranked list of such orientations at the end of each run, and you should be able to scroll through these interactively using the Page/Down and Page/Up (and Home and End) keys on the keyboard. Whether any of these orientations actually represent the right answer, is of course, a completely separate matter!! In any case, if you are not seeing this, it is probably because you need to place the two molecules quite close together before starting the calculation. *Hex* searches over the range of intermolecular separations and angular orientations as specified in the Docking Control panel. If the molecules are initially too far apart, *Hex* will not search over (relatively) small separations unless you specify a large distance range in the docking search. But this will add significantly to the execution time. If you know the location of the ligand binding site, you should manually move the ligand to be close to the binding site (this can be done in *Edit Molecule* mode), and then restrict the receptor rotation angle range to a small value, say 45 degrees. If you know (or have a hunch about) the binding mode of the ligand, you can also use *Edit Molecule* mode to orient the binding surface of the ligand towards the receptor binding site, and then also restrict the ligand rotation angle similarly. When pre-positioning the molecules, it may help to enable the inter-molecular axis display (the double-headed arrow on the right-hand border). This shows the current *z*-axis as a white line, about which the docking is performed. The end-points of this line are the molecular origins (which can also be changed using *Edit Origin* mode). Please also look at the answer given for the previous FAQ.

- *I get a "segmentation fault" when Hex samples protein surfaces prior to a docking run. What's causing this (I'm using an Octane with 640Mb of memory)?*

Surface contouring in *Hex* uses quite a lot of memory, and makes quite a few calls to low-level functions. So even if you have plenty of physical memory, it's possible that you're running out of program stack space. Some system administrators set fairly aggressive `ulimit` values, which limit the resources any individual process can use. You should check, and possibly increase, the values reported by the `ulimit` command (possibly using `ulimit -a` to see them all).

- *I always get a SIGFPE fault towards the end of a Hex docking run on my SGI workstation (IRIX 6.5, 256Mb memory). Can you fix this?*

I would if I could replicate the problem on my O2 machine (IRIX 6.5, 320Mb memory). Despite having IRIX 6.5, it could be that some of your system's run-time libraries are not

up-to-date. I remember a similar “strange” problem on an SGI machine that didn’t have all full set of low-level string handling libraries, and hence failed while reading data files.

If people are willing to send me their data files along with a description of what they’re trying to calculate (preferably as a *Hex* “macro” file), I’ll be happy to try debugging the problem. I will promise not to divulge or otherwise exploit any structures I might receive. But as this example shows, I cannot guarantee a solution!

- *I’m running Hex on a Linux system with an nVidia graphics card. When using nVidia’s 3123 driver, Hex gives a SIGSEG fault when I first run the program, but on subsequent attempts it works fine. With the 4191 driver, Hex starts properly, but solid surfaces seem “broken up”. What’s going on?*

Both of these nVidia drivers are “buggy”. If you can live with the 3123/SIGSEG problem, I’d suggest using that version. The 4191 driver is faster, but drawing surfaces is broken. This is because something changed in the *glX* interface, causing *Hex* to get *no depth buffer!* This has been fixed in *Hex* 3.3. I think nVidia are making a good effort to support Linux, but they do seem to be over-optimising their driver code at the expense of breaking certain basic operations. Or maybe its because I was writing poor code, and just “got lucky” with the earlier versions? Hopefully, such problems will be fixed in future *Hex* and/or driver releases.

- *I can’t get the whole manual to print on my printer. What’s the problem?*

Well, it prints OK on our A4 laser printer. However, both the PDF and HTML versions of the manual use quite a few different fonts, and it may be that your printer has insufficient memory to handle the entire file. Try printing a few pages at a time (say 20), or try changing your printer settings to generate lower quality output. Also ensure that you enable whatever shrink/stretch options are available if you are using a different paper size than A4.

- *What about a Windows version of Hex?*

You probably would not believe how much I hate Windows! But OK, there should be a something ready by late 2003.

# Subject Index

## A

Acknowledgements .....	36
Additional Docking Parameters .....	25
Angular Envelope .....	10
Animation .....	13
Animation Control Panel .....	13
Author .....	36
Axes, Axis .....	5

## B

B Key .....	6
Basic Display Styles .....	7
Batch Docking Example .....	29
BBSRC .....	37
Biological Symmetry .....	8
Bond Widths .....	7
Bugs .....	33
Bumps .....	22
Buttons .....	4, 5
bzip2 .....	30, 37, 45
Bzipped Files .....	30

## C

CAPRI Blind Trial .....	19, 24, 37
Carbo Index .....	26
Cartoon Button .....	5
Cartoon Control Panel .....	9
Cartoons .....	8
Caveats .....	36
Cavities .....	9
Changing The Scene Origin .....	12
Charge Density .....	9
Checkerboard .....	6
Citing Hex .....	38
Clipping .....	12
Clipping Button .....	5
Clipping Clipping The Scene .....	5
Clipping Slider .....	13
Clustering Control Panel .....	22, 23
Clustering Docking Results .....	23
Colour Files .....	7
Colour Ramp .....	9
Colour Schemes .....	7
Colouring Multiple Models Bug .....	34
Command Line Options .....	31
Commercial Licence FAQ .....	52
Complex .....	4, 18
Compressed Files .....	30
Contacts .....	36
Control/C .....	6
Control/Q .....	6
Correlation .....	1

Crystal Symmetry .....	8
------------------------	---

## D

Data Directory .....	43
DCC Stereo Mode .....	48
Density Model .....	2
Disc Cache .....	22
Display Styles .....	7
Distance Range .....	19
Docking Control Panel .....	9, 19, 20, 25, 53
Docking Examples .....	20
Docking Large Molecules .....	24
Docking Molecules .....	17
Docking Motion .....	12
Docking Multiple Structures .....	24
Docking Parameters FAQ .....	53
Docking Results .....	23
Docking Samples .....	21
Docking Summary File .....	23
Docking Transformations File .....	23
Dot Surface Control Panel .....	11
Dot Surfaces .....	7, 11

## E

Edit Origin Mode .....	17
Editing .....	5
Editing Centroids .....	17
Editing Molecules .....	16
Editing Orientations .....	16
Electrostatic Correlations FAQ .....	52
Electrostatic Potential .....	9
Electrostatics .....	1
Environment Variables .....	30, 43
Escape .....	6
Euler Angles .....	16
Examples Directory .....	32, 43

## F

F Key .....	14
False Positives .....	22
FAQs .....	48
Far Plane .....	15
Fast Fourier Transform .....	1
Feature History .....	44
FFT .....	1
File Selection Panel .....	4
Final Search .....	19, 21
FLTK .....	37
Fog .....	7
Fonts .....	5
Frame Rate .....	13

Full Rotational Search .....	20
Full Screen Mode .....	6

## G

G Key .....	14
Gaussian Densities .....	9
Gaussian Surfaces .....	9
Getting Started .....	3
Global Search .....	21
GMP .....	37
Googlisms .....	37
Graphics Menu .....	7
GRASP .....	30
Grid Dimensions .....	20
GUI .....	2
GUI and Graphics Freeze During Docking .....	33
GUI Control Toggle .....	14
gzip .....	30, 37, 45
Gzipped Files .....	30

## H

Hammer Button .....	5, 16
Hardcopy Fonts Bug .....	34
Hardcopy Output .....	30
Harmonic Surface Control Panel .....	10, 34
Harmonics Button .....	5
Harmonics Control Panel .....	11, 24, 35
Hetero Atoms .....	29
Hetero Control Panel .....	18, 29
Hex Licence .....	39
Hex, Dictionary Definition .....	1
Home Position .....	4
Home View .....	6
Hydrogen Atoms .....	7

## I

Icosahedral Tessellation .....	10, 34
ID Button .....	5
Impossible Things .....	1
Installation Guide .....	41
Intermolecular Axis .....	5, 16
Intermolecular Distance .....	6
IRIX .....	36

## K

Keyboard Keys .....	6, 13
Killing Jobs .....	6

## L

Laguerre Polynomials .....	49
Licences .....	38
Ligand .....	4, 18
Ligand Models .....	13
Ligand Orbit .....	19
Ligand Range .....	19
Ligand Translation .....	19
Linux I586/I686 FAQ .....	51
Linux Install FAQ .....	49
Linux Version .....	36

## M

Macro Docking .....	24
Macro-Sampling Control Panel .....	24
Macros .....	27
Macros Bug .....	34
Manoeuvring Molecules .....	15
Marching Tetragons .....	9
Matching Control Panel .....	25
Menu Buttons .....	4, 5
Mesa .....	37
Mesa Install FAQ .....	51
Microsoft Windows Version .....	36
MinGW .....	37
Molecular Centroids .....	12
Molecular Graphics .....	6
Molecular Matching .....	25
Molecular Mechanics Refinement .....	22
Molecular Similarity .....	2
Molecule Control Panel .....	7, 8
MolMol .....	49
Molscript .....	30
Mostly Harmless .....	37
Mouse Buttons .....	4
Movie Type .....	13
MS-Windows .....	36

## N

Near Plane .....	15
NMR Docking .....	24
NMR Models .....	24
No Docking Solutions FAQ .....	54
No Multi-Processing on MS-Windows .....	33
Non-Standard Residues Bug .....	34
Non-Standard Residues FAQ .....	51
nVidia Drivers .....	14
nVidia Graphics Cards .....	14
nVidia Graphics FAQ .....	55
nVidia Stereo Configuration .....	47

**O**

Open Source Projects .....	37
OpenGL Warnings FAQ .....	52
Orientation Control Panel .....	12, 16, 22
Orientation Editing .....	6
Origin Editing .....	6
Origin Editing Button .....	5
Orthographic Projection .....	6, 15
Other Search Modes .....	19

**P**

P Key .....	6
Page/Down .....	6
Page/Up .....	6
Parametric Functions .....	1
PDB .....	4
People .....	37
Perspective Projection .....	6, 15
Picking .....	5
Pipe Output .....	30
Pipes Directory .....	43
Pointer Mode .....	16, 17
Pointer Mode Button .....	5
Polar Hydrogens .....	7
Post Processing Options .....	22
Printing Manual FAQ .....	55
Probe Radius .....	10
Projection Control Panel .....	15

**R**

R Slider .....	6
Radial Cutoff .....	7
Radial Filters .....	20
Receptor .....	4, 18
Receptor Models .....	13
Receptor Range .....	19
RedHat Linux .....	36
Reference Energy FAQ .....	53
Reference Orientation .....	18
References .....	37
Refine Docking FAQ .....	52
Relative Permittivity .....	9
Ribbon Cartoons .....	9
Rotational Search .....	19

**S**

S Key .....	6
Saving Docking Ranges .....	24
Saving Docking Results .....	23
Scene Centre .....	12
SGI Install FAQ .....	51
Shape Matching Scores .....	26
Short-Cut Buttons .....	4
Sidechains Button .....	5, 7
SIGFPE Docking Fault FAQ .....	54

Sigma Surface .....	9
SIGSEG Startup Fault .....	15, 55
SIGSEG Surface Fault FAQ .....	54
Silicon Graphics Version .....	36
Skin Factor .....	12
Slider .....	4
Soft Potentials .....	22
Solid Model Button .....	5
Solid Model Control Panel .....	8
Solid Models .....	7, 8
Solid Motion Button .....	5
Solid Surface Button .....	5
Solid Surfaces .....	7, 9
Solvent Culling .....	30
Source Code FAQ .....	49
Spherical Harmonic Cube .....	35
Spherical Harmonic Functions .....	35
Spherical Harmonic Rotation .....	35
Spherical Harmonic Surfaces .....	5, 7, 10
Spin Angle .....	14
Stereo Displays .....	6, 14, 15
Stereo Parallax .....	15
Steric Scan .....	19, 21
Stride .....	9, 37
Stride Licence .....	41
Sun Graphics Version .....	36
Sun Install FAQ .....	50
SunOS .....	36
Superposing Molecules .....	25
Surface Control Panel .....	20
Surface Skins .....	1
Symmetry Types .....	8

**T**

Tau Surface .....	9
Technical Information .....	35
Tessellation Mesh Order .....	10
Test Functions .....	34
TexInfo .....	37, 45
The Gimp .....	37
Translation Matrices .....	10, 22
Twist Angle .....	19
Twist Samples .....	21

**V**

van der Waals Spheres .....	8
Viewing Large Molecules .....	7
VMD .....	49

**W**

Windows Version FAQ .....	55
Windows XP .....	36

**X**

XFree86..... 37

**Z**

zlib..... 37  
Zoom..... 4